٥

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4. Form Approved.

Land Office

Lease SF 079065

Unit Aztec Total Unit

## AND DEDODTE ON WELLS

| TO DOUGH  | SUBSEQUENT REPORT OF WATER SHUT-OFF   |
|---|---|
| NOTICE OF INTENTION TO DRILL  | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING  |
| NOTICE OF INTENTION TO CHANGE PLANS<br>NOTICE OF INTENTION TO TEST WATER SHUT-OFF.  | SUBSEQUENT REPORT OF ALTERING CASING  |
| NOTICE OF INTENTION TO TEST WATER SHOTEOUT<br>NOTICE OF INTENTION TO RE-DRILL OR REPAIR W   | I SUBSEQUENT KEI OKT OF ALL PROPERTY  |
| NOTICE OF INTENTION TO RE-DRILL ON RELATION TO SHOOT OR ACIDIZE   | SUBSEQUENT REPORT OF ABANDONMENT  |
| NOTICE OF INTENTION TO SHOOT ON ACTUAL CASING   | supplementary well history injection well x   |
| NOTICE OF INTENTION TO ABANDON WELL   | CONVELSION  |
|   |   |
| (INDICATE ABOVE BY  | CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)   |
|   | October 10 , 19 63  |
| SEA Sec. 19 T-2   | ft. from S line and 54.50 ft. from line of sec. 19  |
| (14 Sec. and Sec. No.)  | n Juan  |
| (Field)   | (County or Subdivision)   |
| The elevation of the derrick floor ab   | ove sea level is 5384 ft. G.L. 007 1: 196   |
| The elevation of the derrick floor ab   | 001 To 180  |
|   |   |
|   |   |
| Candernacted depths to objective s  | sands; show sizes, weights, and lengths of proposed casings; indicate shudding jons, commissions, sands; show sizes, weights, and lengths of proposed work)   |
|   | perfalls or works sands; show sizes, weights, and lengths of proposed casings; indicate mudding this coments soints, and all other important proposed work)   |
| led tubing. San 161 jts. 2 sted) Landed at 5,000' RKB. sp seating mipple at 5,000' Full converted and water inject  | 3/8" EUE 4.7% J55 tubing (Internally plastic Bottom of Baker Model "R" packer at 4,999 RKB tion commenced 11-1-02  RECEIVED  OCT1 5 1963 OIL CON. COM. DIST. 3  |
| Hed tubing. Ean 161 jts. 2 ited) Landed at 5,000 RKB. up seating nipple at 5,000 Fill converted and water inject  | 3/8" EUE 4.7% J55 tubing (Internally plastic Bottom of Baker Model "R" packer at 4,999 RKB tion commenced 11-1-02  RECEIVED  OCT1 5 1963 OIL CON. COM.  |
| lied tubing. Tan 161 jts. 2 ited) Landed at 5,000 RKB. ap seating nipple at 5,000 Fill converted and water inject lunderstand that this plan of work must recompany AMERICOL & GAD                          | 3/8" ME 4.7% J55 tubing (Internally plastic Bottom of Baker Model "R" packer at 4,999 RKB tion correnced 11-1-02  RECEIVED  OCT1 5 1963 OIL CON. COM. DIST. 3  ceive approval in writing by the Geological Survey before operations may be commenced.                 |
| led tubing. Ran 161 jts. 2 ited) Landed at 5,000° RKB. In seating nipple at 5,000° Fill converted and water inject tunderstand that this plan of work must recompany AMERIC OFF. & GAD Address DRAKER \$570 | 3/8" ME 4.7% J55 tubing (Internally plastic Bottom of Baker Model "R" packer at 4,999 RKB tion commenced 11-1-02  RECEIVED  OCT1 5 1963 OIL CON. COM. DIST. 3  ceive approval in writing by the Geological Survey before operations may be commenced.  BENJAMIN MEANS |
| lied tubing. Tan 161 jts. 2 ited) Landed at 5,000 RKB. ap seating nipple at 5,000 Fill converted and water inject lunderstand that this plan of work must recompany AMERICOL & GAD                          | 3/8" ME 4.7% J55 tubing (Internally plastic Bottom of Baker Model "R" packer at 4,999 RKB tion commenced 11-1-02  RECEIVED  OCT1 5 1963 OIL CON. COM. DIST. 3  ceive approval in writing by the Geological Survey before operations may be commenced.  BENJAMIN MEANS |