

X			

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Navajo Tribal
Allottee _____
Lease No. **14-22-403-2199**
Navajo Tribal "P"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____	X
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____	
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____	
NOTICE OF INTENTION TO ABANDON WELL _____	Results of Core _____	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Navajo Tribal "P"

Farmington, New Mexico February 7, 1961

Well No. 6 is located 1830 ft. from N line and 640 ft. from W line of sec. 22

SW/4 NW/4 of Section 22 T-29-N R-14-W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Cha Cha Gallup San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5072 ft. (RSD)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Core No. 1 4818-4842 Gallup - Recovered 44' as follows: 16' shale with occasional thin sandy shale laminations, 1' shale and sand with large silt nodules, 11' medium grained friable sand, fair to good porosity with permeability, strong order, nodular shale inclusions 4835-37, shale stringers 4839-48 tighter at 4842-44, 2' tight sandy shale, with 14' slightly sandy shale to shale. Total depth 4930' plugged back depth 4884' set 4 1/2" casing at 4920 with 125 sacks 6 per cent gel cement and 1 1/2 pounds tnf plug per sack, followed by 75 sacks neat cement. Tested casing with 3000 psi which held with no indication of pressure drop. Displaced with 75 barrels oil and 300 gallons H₂O. Released rig January 30, 1961. Preparing for completion operations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Fox American Petroleum Corporation

Address Box 480

Farmington, New Mexico

Attn: L. O. Speer, Jr.

ORIGINAL SIGNED BY
R. M. Bauer, Jr.

By _____

Title Senior Petroleum Engineer

