

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan
Initial X Annual _____ Special _____ Date of Test 4-9-61
Company Redfern & Herd Inc. Lease Maxey Well No. 1
Unit B Sec. 24 Twp. 29N Rge. 12W Purchaser _____
Casing 4 1/2" Wt. 9.5# I.D. _____ Set at 6468 Perf. 6208 To 6336
Tubing 2 3/8" Wt. 4.7# I.D. _____ Set at 6336 Perf. 6334 To 6336
Gas Pay: From 6208 To 6336 L _____ xG 0.680 -GL _____ Bar.Press. _____
Producing Thru: Casing X Tubing _____ Type Well Single-Gas
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: 3-20-61 Packer _____ Reservoir Temp. _____

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter) Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						2090		2094		
1.										
2.										
3.	2"	0.750	553		70	812				3 Hrs.
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.							
2.							
3.	12.3650		565	.9905	.9393	1.064	6916
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})

Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2106 P_c² 4435


No.	$\frac{P_w}{P_t}$ (psia)	P _t ²	F _c Q	(F _c Q) ²	$\frac{(F_c Q)^2}{(1-e^{-s})}$	P _w ²	P _c ² -P _w ²	Cal. P _w	$\frac{P_w}{P_c}$
1.									
2.									
3.	824						3756		1.1808
4.									
5.									

Absolute Potential: 7832 MCFPD; n 1.1325COMPANY Redfern & Herd Inc.ADDRESS Box 1747 Midland, TexasAGENT and TITLE T. A. Dugan, Engineer

WITNESSED _____

COMPANY _____

REMARKS _____



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .