

NEW MEXICO OIL CONSERVATION COMMISSION

NOTICE OF INTENTION TO DRILL

See Rules 101 and 1104.

If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval.



Aztec, New Mexico

July 31, 1952

Place

Date

Notice hereby is given that it is our intention to commence the drilling of a well to be known as.....

Douglas Kenaston Bergin Estate Pooled

V410

in T11N1E1

Company or Operator

Lease

Pool

of Sec. 21, T. 29, R. 11 W., N. M., P. M., Kuts-Fulcher, San Juan County.

The well is 850 feet from (N.) 3 line and 1750 feet from

(E.) (W.) line of the above section.

(Give location from section lines. Cross out wrong directions.)

Lease is W. R. Mints, Aztec, New Mexico

If patented land the owner is Ralph Bergin Estate pooled with
Address Ruth Bergin, Bloomfield, N.M., Douglas C. Wade,
If government land the permittee is Winslow, Arizona and Roy M. Jackson,
Address Glenwood Springs, Colorado

~~W. R. Mints~~ Ralph Bergin Estate 60 acres (1/4 S1/4 NE1/4 & N1/4 NE1/4)

~~W. R. Mints~~ Ruth Bergin 20 acres (1/4 S1/4 NE1/4)
~~W. R. Mints~~ D. C. Wade & R. M. Jackson 60 acres (1/4 S1/4 NE1/4)

We propose to drill well with drilling equipment as follows:

Rotary

The status of a bond for this well in conformance with Rule 101 of the General Rules and Regulations of the Commission is as follows: \$10,000 Blanket Bond on file with the Commission

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
10 3/4	8 5/8	32#	Second Hand	100'	Cemented	50
8 3/4	5 1/2	15 1/2#	" "	1600'	"	100

If changes in the above plans become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 1700 feet.

Additional information: We propose to drill a well to and through the Pictured Cliff sand, estimated depth 1700 feet. A minimum of 100 feet of 8 5/8" casing will be cemented to the surface. Approximately 1600 feet of 5 1/2" casing cemented with approximately 200 sacks; Drill the sand and if conditions warrant 80 to 90 feet of section will be shot with approximately 3 qts. to the foot of 3NG; clean out, run 1 1/2 syphon line to the bottom and complete as gas well.

Approved....., 19.....

except as follows:

SEP 8 1952

Douglas Kenaston

Company or Operator

By W. R. Mints

Position Manager

Send communications regarding well to:

Name W. R. Mints, Aztec, New Mexico

Address

OIL CONSERVATION COMMISSION,

By Al Murr

Title Oil and Gas Inspector Dist. #3.