

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name <b>Gallegos Canyon Unit</b>
2. Name of Operator <b>PAN AMERICAN PETROLEUM CORPORATION</b>		8. Farm or Lease Name
3. Address of Operator <b>501 Airport Drive, Farmington, New Mexico 87401</b>		9. Well No. <b>107</b>
4. Location of Well UNIT LETTER <b>D</b> <b>820</b> FEET FROM THE <b>North</b> LINE AND <b>990</b> FEET FROM THE <b>West</b> LINE, SECTION <b>19</b> TOWNSHIP <b>29-N</b> RANGE <b>12-W</b> NMPM.		10. Field and Pool, or Wildcat <b>Basin Dakota</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>5437' RDB, 5425' GL</b>		12. County <b>San Juan</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to refrac the present perfs at 5937-40' and 5946-52' with 10,000 pounds 20-40 sand, 50,000 pounds 10-20 sand and 2,000 pounds 8-12 glass beads in 30,000 gallons gelled water. A bridge plug will be set at 5925' and the Graneros interval 5856-62' and 5874-84' will be perforated with 3 SPF. This interval will be fraced with 5,000 pounds 20-40 sand, 25,000 pounds 10-20 sand and 2,000 pounds 8-12 glass beads in 15,000 gallons gelled water. The bridge plug will then be drilled out and the well tested.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY **G. W. Eaton, Jr.** TITLE **Area Engineer** DATE **August 28, 1968**  
SIGNED **G. W. Eaton, Jr.**  
APPROVED BY **Erving C. Chaves** TITLE **Sup Dist III** DATE **8-30-68**  
CONDITIONS OF APPROVAL, IF ANY: