

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Basin Natural Gas Corporation

A. C. Hare

(Company or Operator)

(Lease)

Well No. 1, in SW 1/4 of SE 1/4, of Sec. 15, T 29-N, R. 11-W, NMPM.

Pool, San Juan County.

Well is 990 feet from South line and 1650 feet from East line

of Section 15. If State Land the Oil and Gas Lease No. is

Drilling Commenced April 19, 1955. Drilling was Completed June 12, 1955.

Name of Drilling Contractor Rotary--Banner Drilling Co., Farmington.

Address Cable-- F. B. Umbarger, Aztec

Elevation above sea level at Top of Tubing Head. The information given is to be kept confidential until, 19.

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.



CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10 3/4	32	new	60'				Thru quick Sand
8 5/8	32	new	96'				Surface
5 1/2	15	new	1515'	HOWCO			Long String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10 3/4	8 5/8	96'	21 sacks			
8 7/8	5 1/2	1515'	250	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

San Fracs with 5,000 gal. oil, 38 sack sand, 15 gal. Moreflo, Breakdown Pressure 1800 lbs, sejection rate 18 BPM at 1533'. Drilled 15 more feet to TD of 1548 shot 30 quarts of SNG by Reak Glycerin Co. Re-fracs same as above.

Result of Production Stimulation Slight show of gas but not in commercial quantities.

Hole dry.

Depth Cleaned Out 1548

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

ols were used from **96** feet to **1515** feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
ls were used from **0** feet to **96** feet, and from **1515** feet to **1548** feet.

roducing....., 19.....

LL: The production during the first 24 hours was.....M.C.F. plus.....barrels of  
liquid Hydrocarbon. Shut in Pressure.....lbs.

f Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

## Northwestern New Mexico

T. Devonian.....	T. Ojo Alamo.....	550
T. Silurian.....	T. Kirtland-Fruitland.....	none
T. Montoya.....	T. Farmington.....	725
T. Simpson.....	T. Pictured Cliffs.....	
T. McKee.....	T. Menefee.....	
T. Ellenburger.....	T. Point Lookout.....	
T. Gr. Wash.....	T. Mancos.....	
T. Granite.....	T. Dakota.....	
T. ....	T. Morrison.....	
T. ....	T. Penn.....	
T. ....	T. ....	
T. ....	T. ....	
T. ....	T. ....	
T. ....	T. ....	

[illegible]

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

weby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far determined from available records.