

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan
Initial 1 Annual _____ Special _____ Date of Test 6-30-63
Company PAN AMERICAN PETROLEUM CORP. Lease Gallegos Canyon Unit Well No. 134
Unit M Sec. 17 Twp. 29N Rge. 12W Purchaser Pan American Gas Company
Casing 4-1/2 Wt. 10.5 I.D. 4.052 Set at 1741 Perf. 6070-00 To 6080-93
Tubing 2-1/16 Wt. 3.25 I.D. 1.751 Set at 6043 Perf. - To -
Gas Pay: From 6070 To 6092 L 6061 xG 70 est. -GL 4237 Bar.Press. 12
Producing Thru: Casing _____ Tubing 1 Type Well Single
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: 6-26-63 Packer None Reservoir Temp. -

OBSERVED DATA

Tested Through (Gauges) (Choke) (Meters) Type Taps Flange

Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
No.	(Line) (Line) Size	(Choke) (Choke) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.
SI	<u>5 days</u>					<u>2040</u>		<u>2061</u>	
1.	<u>2"</u>	<u>.720</u>	<u>442</u>			<u>531</u>	<u>60° est.</u>	<u>1243</u>	<u>3 hours</u>
2.									
3.									
4.									
5.									

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.3650</u>		<u>442</u>	<u>1.000</u>	<u>.9238</u>	<u>1.037</u>	<u>3948</u>
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})


Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2073 P_c² 4297329

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.						<u>150049</u>	<u>2717229</u>		
2.									
3.									
4.									
5.									

Absolute Potential: 7342 MCFPD; n 0.73
COMPANY PAN AMERICAN PETROLEUM CORPORATION
ADDRESS Box 480, Farmington, New Mexico
AGENT and TITLE F. W. Foell, Petroleum Engineer
WITNESSED _____
COMPANY _____

REMARKS

Shut in pressures were recorded with dead weight tester until two consecutive pressures were obtained.



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .