

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
9. Well No.	
10. Field and Pool, or Wildcat	
12. County	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER- ☐

Name of Operator Manana Gas, Inc. for D. Woodward Stiles

Address of Operator P. O. Box 145, Farmington, N.M. 87499

Location of Well UNIT LETTER M, 1065 FEET FROM THE South LINE AND 1045 FEET FROM THE West LINE, SECTION 13 TOWNSHIP 29N RANGE 11W NMPM.

15. Elevation (Show whether DF, RT, GR, etc.) 5563 GL

RECEIVED

APR 18 1983

OIL CON. DIV.
DIST. 3

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
FORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WELL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Squeeze Fruitland thru existing 2 3/8ths tubine if well does not circulate. Tubing set at 1612' with packer set at 1451'.
- Perforate at 750', which is 50' below Ojo Alamo and set a 100' plug.
- Perforate at 100', which is 50' below base of surface pipe and set 100' plug to surface.
- Set marker and clean location.

All plugs to be of Class A, B, or C neat cement and may be accelerated by up to 3% CaCl.

All plugs will be separated by gel mud of minimum nine pounds per gallon.

OCD office to be notified a minimum of 24 hours before plugging operations are commenced.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

BY Ed Hartman TITLE Pres. DATE 4/18/83

PROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE APR 18 1983