GPO 862040

X

(SUBMIT IN TRIPLICATE)

UNITED STATES **DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY**

Land Office	Sente Fe	
Lease No.	078716	
I Imia	8¥/4	•

	SUI	SSEQUENT REPORT OF WATER SHUT-OFF	3200
NOTICE OF INTENTION TO CHANG		SEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST W	1 11	SEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRII		SEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT		SEQUENT REPORT OF ABANDONMENT.	
NOTICE OF INTENTION TO PULL O		PLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDO	NAL DAVET I		
(INDI	CATE ABOVE BY CHECK MARK NATURE C	F REPORT, NOTICE, OR OTHER DATA)	
		November 18, 1960	10
J. Glenn furner - 'ell No. 17-1 is loc		ine and 1470 ft. from $\frac{1}{W}$ line of se	, 19
/4 Sec. 17		(· ·)	
(½ Sec. and Sec. No.)	T 29-B R-10-W (Twp.) (Range)	(Meridian)	
indesignated Dakota	San Juan County	New Mexico	
(Field)	(County or Subdivisi	on) (State or Territory)	•
	ing points, and all other impor	tunt proposed work)	
vember 10, 1960 - A	udded well at 8:15 P.) ter srilling to man 3 r 8-5/3" in 244 J-55 of coment - 24 calcium		cki
vember 10, 1960 - A c. o.	udded well at 3:15 P. at ter arilling to make 3 f 8-5/3" in 24 f J-55 of coment - 2% calcium urface.	4. 40' RKB, set 10 joints (321.7 easing at 332' RKB with 225 se	eks to
vember 10, 1960 - A c. c. s	udded well at 8:15 P.) ter drilling to man 3:15 P.) f 8-5/3" in 24 J-55 of coment - 24 calcium urface.	4. \$40° RKB, set 10 joints (321.7 seing at 332° RKB with 225 se chloride. Circulated cement	cks to
vesiber 10, 1960 - A	ter arilling to make 3 f 8-5/3" in 24 f J-55 of coment - 2% colorum urface.	i. pho' RKB, set 10 joints (321.7) sacing at 332 RKB with 225 sa chloride. Circulated cement otary rig after cement had se	cks to
vember 10, 1960 - A c. o. s	ter arilling to make 3 f 8-5/3" in 24 f J-55 of coment - 2% colorum urface.	i. pho' RKB, set 10 joints (321.7) sacing at 332 RKB with 225 sa chloride. Circulated cement otary rig after cement had se	cks to
Versiber 10, 1960 - A	ter drilling to make 3 f 8-5/3" in 24 f J-55 of coment - 24 calcium urface. caused drilling with receive approval in writing by	i. pho' RKB, set 10 joints (321.7) sacing at 332 RKB with 225 sa chloride. Circulated cement otary rig after cement had se	cks to