# Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Departmen

Form	c.	10	3
Revis	ed :	1-1	-89

Energy, witherars and war	шш хс	oonoo zopmanon		Revised 1-1-89
OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088		WELL API NO.		
			6 Indiana Trans	-C.T
			5. Indicate Type (	STATE FEE X
			6. State Oil & Ga	s Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS				
IVOIR. USE "APPLICATION F	OR PER		7. Lease Name or	Unit Agreement Name
			Hanley	
OTHER		****		
N			8. Well No.	
	р.		9. Pool name or \	Vildcat
mington, New Mexic	o 874	99	Aztec Pi	ctured Cliffs
50 Feet From The Sout	h	Line and 990	Feet From	The West Line
29N	D.,,	· 10W	San S	Juan
		ige , r	IMPM	County
Appropriate Box to Indi	icate N	lature of Notice. Re	port or Other	· Data
** *		•	• •	
	(X)			۲
		HEMEDIAL WORK		ALTERING CASING L
CHANGE PLANS	$\sqcup$	COMMENCE DRILLING OPNS. L PLUG AND ABANDONMENT L		
		CASING TEST AND CEMENT JOB		
		OTHER:		
ions (Clearly state all pertinent de	etails, and	d give pertinent dates, includ	ing estimated date o	f starting any proposed
d to plug and aban	don w	ell.		
t for information.		we will be a second	n 4 12 2 3	1 77 FM
				ÿ . 
			AFRE 7 199	9
		في حمي	事。25月8日春	
		*	• • • • • • • • • • • • • • • • • • • •	
			ရည်ချိန်မြင် နှင့် (၂)	
ORPORATION				
and complete to the best of my knowl UNIGHAL STORED BY EWELL IN WASSE	edge and b	<sup>xdid</sup> President, Wa & Prod. Corp.	lsh Engr.	DATE4/27/89
and complete to the best of my knowl	ledge and b	<sup>xdid</sup> President, Wa & Prod. Corp.	lsh Engr.	date4/27/89 Telephone no.
EWELL N WASSH	iodge and b	e a Prod. Corp.		TELEPHONE NO.
and complete to the best of my knowl UNIGHAL STORED BY EWELL IN WASSE	ledge and b	DEPUTY CIL & GAS I		TELEPHONE NO.
	P.O. B. Santa Fe, New M. CES AND REPORTS OF POSALS TO DRILL OR TO DRIVOIR. USE "APPLICATION FOR SUCH PROPOSALS OTHER  N Engr. & Prod. Cormington, New Mexic  50 Feet From The Sout Township 29N  10. Elevation (Show) 5576 GR  Appropriate Box to Individual Section (Change Plans)  CHANGE PLANS	P.O. Box 208  Santa Fe, New Mexico  CES AND REPORTS ON WELDPOSALS TO DRILL OR TO DEEPEN ROOK. USE "APPLICATION FOR PER-101) FOR SUCH PROPOSALS.)  OTHER  N  Engr. & Prod. Corp. mington, New Mexico 874  50 Feet From The South  Township 29N Ram  10. Elevation (Show whether I 5576	P.O. Box 2088 Santa Fe, New Mexico 87504-2088  CES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A RVOIR. USE 'APPLICATION FOR PERMIT'-101) FOR SUCH PROPOSALS.)  OTHER  N  Engr. & Prod. Corp. mington, New Mexico 87499  50 Feet From The South Line and 990  Township 29N Range 10W N  Township 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5576' GR  Appropriate Box to Indicate Nature of Notice, Reference o	P.O. Box 2088  Santa Fe, New Mexico 87504-2088  5. Indicate Type of 6. State Oil & Ga CES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name of Novoir. USE "APPLICATION FOR PERMIT" 101) FOR SUCH PROPOSALS.)  Hanley  OTHER  8. Well No. 1  Engr. & Prod. Corp.  mington, New Mexico 87499  50 Feet From The  South  Line and  990  Feet From  Township  29N  Range 10W  NMPM  San 3  10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5576 GR  Appropriate Box to Indicate Nature of Notice, Report, or Other ENTION TO:  PLUG AND ABANDON  REMEDIAL WORK  CHANGE PLANS  CASING TEST AND CEMENT JOB  OTHER:  Lions (Clearly state all pertinent details, and give pertinent dates, including estimated date of the plug and abandon well.



#### DAMSON OIL CORPORATION HANLEY NO. 1 1650'FSL, 990'FWL, SECTION 18-T29N-R10W San Juan County, New Mexico

#### Estimated Formation Top

Ojo Alamo	560'
Base Ojo Alamo and Top of Kirtland Farmington Fruitland Pictured Cliffs P.B.T.D.	780' 1080' 1489' 1890' 1937'

#### Present Completion

- 1. 35 sack cement plug in 8-3/4" hole, 1937' to 2024'.
- 2. 7" casing set at 1887' with 125 sacks cement. Calculated top of cement at 1000'.
- 3. Shot open hole, 1895' 1937', with 120 quarts.

### Proposed Plugging Procedure

- 1. Set 50 sack cement plug from 1787' to 1937'. (7" casing and open hole)
- 2. Set 25 sack cement plug in 7" casing, 1300' 1400'.
- 3. Perforate, 4 holes, at 830' (50' below base of Ojo Alamo). Set 75 sack cement plug inside and outside 7" casing.
- 4. Fump 25 sacks cement in bradenhead between surface casing and 7" casing.
- 5. Cut off surface casing and 7" casing 2 feet below gound level.
- 6. Set 4 inch marker with 4 feet above ground level with 10 sacks cement.