

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Hanley

8. Well No.  
1

9. Pool name or Wildcat  
Aztec Pictured Cliffs

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
DAMSON OIL CORPORATION

3. Address of Operator c/o Walsh Engr. & Prod. Corp.  
P. O. Drawer 419 Farmington, N.M. 87499

4. Well Location  
Unit Letter L : 1650 Feet From The South Line and 990 Feet From The West Line

Section 18 Township 29N Range 10W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

5576' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10/22/90 Kill well. Set 50 sack cement plug 1690' to 1890'.

10/23/90 Tag cement plug at 1840'. 7" casing set at 1887'. Pressure test casing and cement plug - 200 psig. Test ok. Spot 25 sack cement plug 1307' to 1407'. Perforate 790' to 792' with 2 shots per foot, 4 holes. Spot 100 sack cement plug 650' to 790'. Cement equalized through perforations. Spot 25 sack cement plug 130' to 230'. Squeeze bradenhead with 25 sacks.

10/24/90 Cut off wellhead and install dry hole marker.

FOR: DAMSON OIL CORPORATION

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE EWELL N. WALSH TITLE Agent DATE 10/24/90

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

Original Signed by CHARLES GHOLSON

DEPUTY OIL & GAS INSPECTOR, DIST. #3

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 10/26/1990

CONDITIONS OF APPROVAL, IF ANY: