

SP


(SUBMIT IN TRIPLICATE)

Land Office _____

Lease No. 079509

Unit Neudecker

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 23, 1957

Well No. 1 is located 990 ft. from N line and 1650 ft. from E line of sec 14
NW Sec. 14 29N 10W N.M.F.M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Aztec P. C. San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6005 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7-29-57 E. L. Chilton & Son Rig #1 moving on location and rigging up. Rocking 129 joints 2" EUE tubing.
 7-30-57 Cleaning out bridge from 2400 to 2412 and 2529 to 2565.
 7-31-57 Set Baker Model K, cast iron retainer @ 3347'. Plugged off M.V. with 200 sacks Neat cement. Displaced cement to 3900'. Dropped bridging ball into cement retainer, thus making the cement retainer a permanent plug.
 8-1-57 Perforated 5 1/2" casing at 2552-53 and 2300-01 (4 jets/ft.) Set Baker Model K cast iron retainer @ 2536'. Squeezed 100 sacks Neat cement thru lower perms. (did not have circulation) Dropped bridging ball and made the cement retainer a permanent plug.
 8-2-57 Set retrievable ret. @ 2188'. Squeezed perf. 2300 (4 holes) w/150 sks, final pr. 2300#.
 8-4-57 T. D. 4785', P.B.T.D. 2301' water frac. P. C. int. 2414-54 (2/SPP) w/38,000 gal. water and 40,000# sand, flush 3000 gal. ED - none; max. tr. pr. 1700#, avg. tr. pr. 1700#, I. R. 68 BEM.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. (over)

Company El Paso Natural Gas Company

Address Box 997

Farmington, New Mexico

By _____

Title Petroleum Engineer

8-5-57 Ran 118 joints 1 1/4", 2.3# Grade 'B' line pipe, landed at 2473'.
8-16-57 Date well was tested.