Form	9-331 a
(Feb	. 1951)

i		_
		I

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa Po
Lease No	078110
Unit	
Unit	

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
few Mexico Federal "I"	November 9 , 1961
Vell No. 6 is located 510 ft. from	m. $\{N\}$ line and 555 ft. from $\{E\}$ line of sec. 15
(E) of NEi, Sec. 15 29H	THE MAPS
(½ Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
To should have write	Juan How Maximo
(Field) (County	y or Subdivision) (State or Trritor NOV1 4 196
ne elevation of the derrick floor above sea l	
he elevation of the derrick floor above sea in	level is   OIL CON. CO
DETA	AILS OF WORK \ DIST. 3
Duir	
take names of and expected depths to objective sands: show to	sizes, weights, and lengths of proposed casings; indicate mudding jobs, comen
take names of and expected depths to objective sands: show to	sizes, weights, and lengths of proposed casings; indicate mudding jobs, comen il other important proposed work)
itate names of and expected depths to objective sands; show a ing points, and al	sizes, weights, and lengths of proposed casings; indicate mudding jobs, comen il other important proposed work)
tate names of and expected depths to objective sands; show a ing points, and al	sizes, weights, and lengths of proposed casings; indicate mudding jobs, comen
tate names of and expected depths to objective sands; show a ing points, and all	sizes, weights, and lengths of proposed casings; indicate mudding jobs, committed the important proposed work)
tate names of and expected depths to objective sands; show a ing points, and all 12% hale was drilled to 510%.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, considered in the important proposed work)  1.5/8" (1) 21/2 J-55 casing was set at 502°  1.5/8" (1) 21/2 J-55 casing was set at 502°  1.5/8" (2) thre, test cage to 1000/ for 30 min. A
tate names of and expected depths to objective sands; show a ing points, and all 12% hule was drilled to 510%.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, considered in the important proposed work)  1.5/8" (1) 21/2 J-55 casing was set at 502°  1.5/8" (1) 21/2 J-55 casing was set at 502°  1.5/8" (2) thre, test cage to 1000/ for 30 min. A
tate names of and expected depths to objective sands; show a ing points, and all 122" hule was drilled to 510°. & 1/h00 sanks, coment circulated. WCC 7-7/8" hole was drilled to 5160.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, commit other important proposed work)  6-5/8" © 24# J-55 casing was set at 502°  C 24 hrs, test cag. to 1000# for 30 min. A
tate names of and expected depths to objective sands; show a ing points, and all 122" hule was drilled to 510°. & 1/h00 sacks, coment circulated. WCC 7-7/8" hole was drilled to 5160.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, considered in the important proposed work)  1.5/8" (1) 21/2 J-55 casing was set at 502°  1.5/8" (1) 21/2 J-55 casing was set at 502°  1.5/8" (2) thre, test cage to 1000/ for 30 min. A
tate names of and expected depths to objective sands; show a ing points, and all 122" hale was drilled to 510". Ex/600 sanks, coment circulated. WCC 1-7/8" hale was drilled to 5160. Sec/100 sanks Incor cat. with his gal,	sizes, weights, and lengths of proposed casings; indicate mudding jobs, commit other important proposed work)  5/8" (1) 24/8 J-55 casing was set at 502'  C 24 hrs, test esg. to 1000/ for 30 min. A  5/8" (1) 14/8 15.5% J-55 casing set at 5160'  2 % CoCl2 & 12/9 (ilsenite per seck, follo
tate names of and expected depths to objective sands; show a ing points, and all 12% hale was drilled to 510%. Ex/500 sanks, coment circulated. WCC 7-7/8" hale was drilled to 5160. Sec/100 sanks Incor cat. with his gal,	sizes, weights, and lengths of proposed casings; indicate mudding jobs, commit other important proposed work)  6-5/8" © 24# J-55 casing was set at 502°  C 24 hrs, test cag. to 1000# for 30 min. A
tate names of and expected depths to objective sands; show a ing points, and all 122" hale was drilled to 510". En/h00 sacks, coment circulated. WCC 7-7/8" hale was drilled to 5160. Se/100 sacks Incor cat. with h5 gal, with 50 sm. mest, 2% CaCl2 & 0.7% is	sizes, weights, and lengths of proposed casings; indicate mudding jobs, commit other important proposed work)  5/8" (1) 24/8 J-55 casing was set at 502'  C 24 hrs, test esg. to 1000/ for 30 min. A  5/8" (1) 14/8 15.5% J-55 casing set at 5160'  2 % CoCl2 & 12/9 (ilsenite per seck, follo
itate names of and expected depths to objective sands; show a ing points, and all A 12½" hule was drilled to 510°. Ex/h00 sanks, coment circulated. WCC 7-7/8" hole was drilled to 5160. Sec/100 sanks Incor cat. with his gal,	sizes, weights, and lengths of proposed casings; indicate mudding jobs, commit other important proposed work)  5/8" (1) 24/8 J-55 casing was set at 502'  C 24 hrs, test esg. to 1000/ for 30 min. A  5/8" (1) 14/8 15.5% J-55 casing set at 5160'  2 % CoCl2 & 12/9 (ilsenite per seck, follo
tate names of and expected depths to objective sands; show a ing points, and all 12; hale was drilled to 510. Ex/600 sanks, coment circulated. WCC 7-7/8" hale was drilled to 5160. Sec/100 sanks Incor cmt. with his gel, with 50 sm. meat, 2% CaCl2 & 0.7% of the casing to 1000/ for 30 min.  I understand that this plan of work must receive approval	sizes, weights, and lengths of proposed casings; indicate mudding jobs, confil other important proposed work)  1. 5/8" (1) 21/2 J-55 casing was set at 502'  1. 21/2 hrs, test cag. to 1000/ for 30 min. A  5/3" (1) 11/4 & 15.5/2 J-55 casing set at 5160'  2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  2 // Cacl2 & 12/4 (ilsonite per sack, followable)
tate names of and expected depths to objective sands; show a ing points, and all 122" hale was drilled to 510". Ex/h00 sacks, coment circulated. WCC 7-7/8" hale was drilled to 5160. Sc/100 sacks Incor cut. with his gel, with 50 sm. meat, 2% CaCl2 & 0.7% of the 50 sm. meat, 2% CaCl2 & 0.7% of the 50 sm. meat, 2% CaCl2 & 0.7% of the 50 sm. meat, 2% CaCl2 & 0.7% of the 50 sm. meat, 2% CaCl2 & 0.7% of the 50 sm. meat, 2% CaCl2 & 0.7% of the 50 sm.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, confil other important proposed work)  1. 5/8" (1) 21/2 J-55 casing was set at 502'  1. 21/2 hrs, test cag. to 1000/ for 30 min. A  5/3" (1) 11/4 & 15.5/2 J-55 casing set at 5160'  2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  2 // Cacl2 & 12/4 (ilsonite per sack, followable)
tate names of and expected depths to objective sands; show a ing points, and all a light to slow a drilled to slow. It is a light to slow a drilled to slow. It is a light to slow a drilled to slow. It is a light to sand a light to slow a drilled to slow. It is a light to sand a light to sand a light to sand a light to slow a light to sand a light t	sizes, weights, and lengths of proposed casings; indicate mudding jobs, confil other important proposed work)  1. 5/8" (1) 21/2 J-55 casing was set at 502'  1. 21/2 hrs, test cag. to 1000/ for 30 min. A  5/3" (1) 11/4 & 15.5/2 J-55 casing set at 5160'  2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  1. 2 // Cacl2 & 12/4 (ilsonite per sack, followable)  2 // Cacl2 & 12/4 (ilsonite per sack, followable)
tate names of and expected depths to objective sands; show a ing points, and all 122" hale was drilled to 510". Ex/100 sacks, occurs circulated. WCC 1-7/8" hole was drilled to 5160. Second Incor ent. with his galactic casing to 1000/ for 30 min.  I understand that this plan of work must receive approval company	sizes, weights, and lengths of proposed casings; indicate mudding jobs, confident important proposed work)  1.5/8" (2) 21/2 J-55 casing was set at 502'  2.1 hrs, test cag. to 1000/ for 30 min. A  51 ° (3) 11/4 a 15.5% J-55 casing set at \$160'  2.2 Cacl2 a 12/4 (illective per sack, following by the Geological Survey before operations may be commenced.  Company  ORIGINAL SIGNED BY
122" hale was drilled to 510'. Ex/100 sacks, coment circulated. WX 7-7/8" hale was drilled to 5160. Ex/100 sacks, coment circulated. WX 7-7/8" hale was drilled to 5160. Ex/100 sacks Incor cut. with his gal, with 50 sm. meet, 2% Ca612 & 0.75 Exted casing to 1000% for 30 min.  I understand that this plan of work must receive approval company.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, commit other important proposed work)  1.5/8" (2) 21/ J-55 casing was set at 502'  2.1 hrs, test cag. to 1000/ for 30 min. A  51" (2) 11/ a 15.5/ J-55 casing set at 5160'  2 / Cacl2 a 12// (11semite per cack, following set at 5160')  2 / Cacl2 a 12// (11semite per cack, following set at 5160')  2 / Cacl2 a 12// (11semite per cack, following set at 5160')  Company  ORIGINAL SIGNED BY
tate names of and expected depths to objective sands; show a ing points, and all 122" hale was drilled to 510". Ex/600 sanks, coment circulated. WCC 1-7/8" hole was drilled to 5160. Sec/100 sanks Incor ent. with his galactic casing to 1000/ for 30 min.  I understand that this plan of work must receive approval company	sizes, weights, and lengths of proposed casings; indicate mudding jobs, consider the proposed work)  1. 5/8" (1) 21/8 J-55 casing was set at 502'  1. 21/8 hrs, test cag. to 1000 for 30 min. A  51° (1) 11/8 a 15.5% J-55 casing set at 5160'  2 % Cacl2 a 12/8 (illective per seck, following by the Geological Survey before operations may be commenced.  Company  ORIGINAL SIGNED BY