Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

Form 9-881a (Feb. 1951) X

1-D 1-1

(SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	
Lease No.	SF-078716-A
Unit	
Hubbell	Federal

## SUNDRY NOTICES AND REPORTS ON WELLS

I Morrow		CURCO	
NUTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO TEST WATER SHUT	I-OFF	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
MOTICE OF INTENTION TO RE-DRILL OR REP.	AID WELL	SOUSEGUEN! REPORT OF ALTERING CASING	ļ
THO TICE OF INTENTION TO SHOOT OR ACIDIZ	F	STATE OF RE-DRILLING OR REPAIR	
MORICE OF INTENTION TO PULL OR ALIER C.	ASING	SOUSEQUENT REPORT OF ABANDONMENT	1
NOTICE OF INTENTION TO ABANDON WELL		SUPPLEMENTARY WELL HISTORY	
(INDICATE ABOVE	BY CHECK MARK NAT	URE OF REPORT, NOTICE, OR OTHER DATA)	
			_
	•	April 10	, 19 <u>63</u>
'ell No. 1 is located 80	ft. from S	line and 1840 ft. from W line of sec	. 7
E/4 SW/4 Sec. 7 (½ Sec. and Sec. No.)	9 N 10 W	NAPM	
mestu nskofs		(Meridian)	
(Field)	San Juan (County or Subd	(vision) New Mexico	77 7 17
a alamatian of all a second		(State or Territory)	
ne elevation of the derrick floor a	bove sea level is	5665 ft GL	
			$T^{**}(x,y) \in F$
ite names of and owner at 1	DETAILS (	OF WORK	
and expected depths to objective	sands; show sizes, wele	1.	
ing p	oints, and all other in	nts, and lengths of proposed casings, indi-	
ing p	oints, and all other im	this, and lengths of proposed casings; indicate mudding job portant proposed work)	be, coment-
32.75# casing	3 3/4" surfa @ 225' KB w/	nts, and lengths of proposed casings; indicate mudding join portant proposed work)  100 hole. Ren and set 216 10 3/4  150 ex 2% calcium chloride, left culated. Plugged down 6:30 AM  100# for 30 min. held 0K. Drilling	401
32.75# casing cement in pipe W.O.C. 10 hrs.	13 3/4" surfa @ 225' KB w/ . Cement cir . Tested w/7	150 ex 2% calcium chloride, left culated. Plugged down e 6:30 AM 00# for 30 min. held OK. Drillin	401
32.75# casing cement in pipe W.O.C. 10 hrs.	13 3/4" surfa © 225' KB w/ P. Cement cir Tested w/7	150 ex 2% calcium chloride, left culated. Plugged down e 6:30 AM 00# for 30 min. held OK. Drillin	4" 40' 9th.
32.75# casing cement in pipe W.O.C. 10 hrs.	13 3/4" surfa © 225' KB w/ P. Cement cir Tested w/7	150 ex 2% calcium chloride, left culated. Plugged down e 6:30 AM OO# for 30 min. held OK. Drilling APR1 2 1963  APR1 2 1963  The Geological Survey April 2 1963.	4" 40' 9th.
32.75# casing cement in pipe W.O.C. 10 hrs.  Inderstand that this plan of work must receive pany Southwest Productions 234 Petr. Club Plaza	13 3/4" surfa # 225' KB w/ b, cement cir Tested w/7'	150 ex 2% calcium chloride, left culated. Plugged down e 6:30 AM COM for 30 min. held OK. Drilling APR1 2 1963  APR1 2 1963  APR1 2 1963  Original signed by	4" 40' 9th.
32.75# casing cement in pipe W.O.C. 10 hrs.	13 3/4" surfa # 225' KB w/ b, cement cir Tested w/7'	150 ex 2% calcium chloride, left culated. Plugged down e 6:30 AM OO# for 30 min. held OK. Drilling APR1 2 1963  APR1 2 1963  The Geological Survey April 2 1963.	4" 40' 9th.