(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Santa - Fe
Lease No 065557
Unit DF/4 SEC

		_
OTICE OF INTENTION TO DRILL	 	i i
OTICE OF INTENTION TO CHANGE PLANS		i i
OTICE OF INTENTION TO TEST WATER SHUT-OFF		1 1
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		
OTICE OF INTENTION TO PULL OR ALTER CASING	1.35 11	
IOTICE OF INTENTION TO ABANDON WELL		
(INDICATE ABOVE BY CHECK M	IARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
		, 19.53
ell No 12 is located 1690 ft. f	rom_{-} $\left\{ \begin{array}{c} S \end{array} \right\}$ line and $\frac{1}{2}$	line of sec.
7 (FB and Sec. No.)	12 Host Helichellen	
	(Menual)	<u> </u>
whether Burger Kudz San Jungood	nty or Subdivision) (State o	r Territory)
ne elevation of the derrick floor above see	level is 5724 ft. (5711 plan	s 13')
	TAILS OF WORK	of the orange of
		Table Match
ate names of and expected depths to objective sands; sho ing points, and	M SIXES, Maigitts, Mild feithers or brobosest ensurings, in	areas maderial Jone, comeno.
	all other important proposed work)	
2001 - 20 76 8 1-66 1	ALIAN mertion assist in 12-1	// bale. circula
approx. 120' of 32.75#, 3-55, 1	0-3/4" surface casing in 13-3	// hale, circula
approx. 120' of 32.750, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. was	0-3/4" surface easing in 13-3 ext-off. Drill 8-3/4" hole using conventional core barrell.	/h" bole, circulating and to top of Reen to Militing
approx. 120' of 32.750, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. was	0-3/4" surface easing in 13-3 ext-off. Drill 8-3/4" hole using conventional core barrell.	/h" bole, circulating and to top of Room to Militing
approx. 120' of 32.75%, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. was the with 8-3/4" bit, run and count to be performed with rotary to	0-3/% surface easing in 13-3 ext-off. Drill 8-3/% hole using conventional core barrell, it approx. 1800' of 200, 3-55, No. Heve on cable tools, dri	/h" bels, circula ing sud to top of Rees to fixing
approx. 120' of 32.750, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. was	0-3/% surface easing in 13-3 ext-off. Drill 8-3/% hole using conventional core barrell, it approx. 1800' of 200, 3-55, No. Heve on cable tools, dri	/h" bels, circula ing sud to top of Rees to fixing
approx. 120° of 32.756, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. wast with 8-3/4" bit, run and count to be performed with rotary too. 3., elean out to bottom and run	0-3/% surface easing in 13-3 ext-off. Drill 8-3/% hole using conventional core barrell, it approx. 1800' of 200, 3-55, No. Heve on cable tools, dri	/h" bels, circula ing sud to top of Rees to fixing
approx. 120° of 32.756, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. wast with 8-3/4" bit, run and count to be performed with rotary too. 3., elean out to bottom and run	0-3/% surface easing in 13-3 ext-off. Drill 8-3/% hole using conventional core barrell, it approx. 1800' of 200, 3-55, No. Heve on cable tools, dri	/h" bole, circula ing sud to top of Reen to filling To All of above
approx. 120' of 32.75%, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. was the with 8-3/4" bit, run and count to be performed with rotary to	0-3/% surface easing in 13-3 ext-off. Drill 8-3/% hole using conventional core barrell, it approx. 1800' of 200, 3-55, No. Heve on cable tools, dri	/h" bole, circula ing sud to top of Reen to filling To All of above
approx. 120° of 32.756, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. wast with 8-3/4" bit, run and count to be performed with rotary too. 3., elean out to bottom and run	0-3/% surface easing in 13-3 ext-off. Drill 8-3/% hole using conventional core barrell, it approx. 1800' of 200, 3-55, No. Heve on cable tools, dri	/h" hole, circulating and to top of Reen to Military
epprox. 120° of 32.75%, 3-55, 3 mt to surface, test for water st, send. Core for top of P.C. wast with 8-3/4" bit, run and count to be performed with rotary too 3., elean out to bettom and run	0-3/k" surface easing in 13-3 int-off. Drill 8-3/k" hole us ing conventional core barrell. it approx. 1800' of 20%, 4-55; ils. Heve on cable tools, dri 1" tabing.	// hele, circulating and to top of Rees to Miller about 11 send, shoot wi
approx. 120° of 32.756, 3-55, 3 mt to surface, test for water st send. Core for top of P.C. wast with 8-3/4" bit, run and count to be performed with rotary too. 3., elean out to bottom and run	0-3/k" surface easing in 13-3 int-off. Drill 8-3/k" hole us ing conventional core barrell. it approx. 1800' of 20%, 4-55; ils. Heve on cable tools, dri 1" tabing.	// hele, circulating and to top of Rees to Miller about 11 send, shoot wi
epprox. 120° of 32.75%, 3-55, 3 mt to surface, test for water st, send. Core for top of P.C. wast with 8-3/4" bit, run and count to be performed with rotary too 3., elean out to bettom and run	0-3/k" surface easing in 13-3 int-off. Drill 8-3/k" hole us ing conventional core barrell. it approx. 1800' of 20%, 4-55; ils. Heve on cable tools, dri 1" tabing.	// hele, circulating and to top of Rees to Miller about 11 send, shoot wi
approx. 120° of 32.75°, 3-55, 1 mt to surface, test for water at send. Core for top of P.C. unit with 8-3/4" bit, run and commit to be performed with rotary too G., clean out to bottom and run I understand that this plan of work must receive approximately.	0-3/4" surface casing in 13-1 int-off. Drill 5-3/4" hole us in conventional core barrell. it approx. 1800' of 205, 3-55, ils. Hove on cable tools, dri l' tabling.	// hele, circulating and to top of Rees to Miller about 11 send, shoot wi
epprox. 120° of 32.75°, 3-55, 3 mt to surface, test for water at send. Core for top of P.C. using with 8-3/6" bit, ren and count to be performed with rotary too 3., elean out to bettom and run In 10/29/53 I understand that this plan of work must receive approximately the surface of the su	0-3/4" surface casing in 13-1 int-off. Drill 5-3/4" hole us in conventional core barrell. it approx. 1800' of 205, 3-55, ils. Hove on cable tools, dri l' tabling.	// hele, circulating and to top of Rees to Military T. All of about the contract of the circulation of circulation of the circulation of the circulation of circulati
approx. 120° of 32.75°, 3-55, 1 mt to surface, test for water at send. Core for top of P.C. unit with 8-3/4" bit, run and commit to be performed with rotary too G., clean out to bottom and run I understand that this plan of work must receive approximately.	0-3/4" surface casing in 13-1 int-off. Drill 5-3/4" hole us in conventional core barrell. it approx. 1800' of 205, 3-55, ils. Hove on cable tools, dri l' tabling.	// hele, circulating and to top of Rees to Militing 7°. All of about 11 send, shoot w
approx. 120° of 32.756, 3-55, 1 mt to surface, test for water at send. Core for top of P.C. was to with 8-3/6" bit, run and commit to be performed with rotary too 3., elean out to bottom and run The surface of the s	0-3/4" surface casing in 13-1 int-off. Drill 5-3/4" hole us in conventional core barrell. it approx. 1800' of 205, 3-55, ils. Hove on cable tools, dri l' tabling.	// hele, circulating and to top of Roses to Military and Tabo. The All of about w

et in the second second section of the second

ease	Carroll-Cornell	Well No	12	
ec. 11 T	29 N. , R.	L2 W., N.M.F	.M.	
ocation 1090' from	n the South lir	ne and 9901 f	'rom	
the East 1	-	1.		
levation				
an Juan County		New Mexic	o	
				
			*	
		1		I DOMENICAL SUMMEN
	 (") 			FAPMINGTON: No the
				CHA CHA
			990'- N	
		,°		
		9/		
cale—4 inches equal 1	mile.		,	67
his is to certify that t f actual surveys made	by me or under my	supervision and t	hat the	
ame are true and corre	ect to the best of my	knowledge and b		76
	Geneal	19 Ca	lishe	t V. Echohawk
eal:	Registered Engineer and	Professional- Land Surveyor.		x. Reg. No. 1545