

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in **QUINTUPLICATE** If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Midwater Oil Company (Company or Operator) N. Mex. Federal Lease Unit 12 E
Well No. 1, in NE 1/4 of SE 1/4, of Sec. 12, T. 29N, R. 11W, NMPM.
Undesignated (Dakota) Pool, San Juan County.
Well is 2120 feet from South line and 1650 feet from East line
of Section 12. If State Land the Oil and Gas Lease No. is
Drilling Commenced June 15, 1961 Drilling was Completed July 1, 1961
Name of Drilling Contractor Great Western
Address Box 1659, Midland, Texas
Elevation above sea level at Top of Tubing Head 5768 The information given is to be kept confidential until
Not confidential, 19

OIL SANDS OR ZONES

No. 1, from 6497 to 6516 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet
No. 2, from to feet
No. 3, from to feet
No. 4, from to feet

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	20.0	New	129	Tex. Patn.		None	Surface
4-1/2	11.6	New	913				
4-1/2	9.5	New	5806	Float	6497-6516		Oil String
2-3/8	4.7	New	6463				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/2	8-5/8	129	100	Pump		
7-7/8	4-1/2	6719	600	Pump		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidized with 500 gallons acid, fractured with 40,000# 20-40 sand and 40,000 gallons J-101 water treatment chemical. Dropped 170 balls. Fractured with 20,000# 20-40 sand and 20,000 gallons water.

Result of Production Stimulation 3665 MCF/Day



Depth Cleaned Out

6650'