

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Santa Fe**  
Lease No. **073197**  
Unit **1/2**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 22, 1960

**SE Turner-Rye**  
Well No. **8-2** is located **1600** ft. from **[N]** line and **1630** ft. from **[E]** line of sec. **8**  
**NE/4 Section 8** **T 29-N** **R 10-W** **N.M.P.M.**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Basin Dakota** **San Juan County** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **5,791** ft.


DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

December 14, 1960. Spudded well at 7:30 p.m.

December 15, 1960. After drilling to 365' at NCB., set 11 joints 8-5/8" OD 24# J-55 casing at 360' with 225 sacks 50/50 pozzix, 2% calcium chloride.

After waiting for cement to set - continued drilling with rotary rig.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **J. Glenn Turner**  
**Box 726**  
Address **Farmington, New Mexico.**

By **C. Deacon Neal**  
C. Deacon Neal, Agent in Farmington  
Title