STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVISION

30-045-08566

Well

Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-MEAKAGE TEST DUT

perator <u>B</u>	URLINGTON RESOURCE	Lease NYE FEDERAL			No. <u>2</u>				
_ocation									
of Well:	Unit G Sect	08 Twp.	029N	Rge.	010W	County	SAN JUAN		
		NAME OF RESERVOIR OR POOL				METH	OD OF PROD.	PROD. MEDIUM	
					(Oil or Gas)		w or Art. Lift)	(Tbg. or Csg.)	
Upper Completion	MESAVERDE				Gas	Flow		Tubing	
Lower Completion	DAKOTA				Gas Flov		Flow	Tubing	
	<u> </u>	PRE-I	FLOW SHUT-II	N PRES	SURE DATA				
Upper	Hour, date shut-in Length of time shut-in		SI p	SI press. psig		Stabilized? (Yes or No)			
Completion	6/18/99	120 Ho	urs	322					
Lower Completion	6/18/99	72 Ho	urs		320				
			FLOW TE	ST NO.	1				
Commenced	Commenced at (hour,date)* 6/21/99					Zone producing (Upper or Lower) LOWER			
TIME	LAPSED TIME	PRESSURE			PROD. ZONE				
(hour,date)	SINCE*	Upper Completion	Lower Completion		ТЕМР		REM	fARKS	
6/22/99	96 Hours	322	120						
6/23/99	120 Hours	322	132						
							·		
Production rat	e during test								
Oil:	BOPD based on	used on Bbls. in		Hours.		Grav.	Grav. GOR .		
Gas:		MCFPD; Tested thru	(Orifice or Mete	er): 					
		MID-	TEST SHUT-IN	N PRESS	SURE DATA				
Upper Completion	Hour, date shut-in	Length of time shut-in		SI p	ress. psig		Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	Length of time shut-in		SI press. psig			Stabilized? (Yes or No)		

(Continue on reverse side)

ET OU TECENIO A

			CLOW TEST NO		· · · · · · · · · · · · · · · · · · ·				
Commenced at (hour, d	ate)**			Zone producing (Upper or Lower):					
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	REMARKS				
		Upper Completion	Lower Completion	TEMP.	REMARKS				
				·					
						· · · · · · · · · · · · · · · · · · ·			
						<u></u>			
Production rate du			DI .						
Oii:	BC	OPD based on	Bols. in	Hours	Grav	GOR			
Gas:		MCFPI	D: Tested thru (Orif	ce or Meter):		 			
Remarks:			· · · · · ·						
I hereby certify the	at the information has	rain contained is true	and complete to the	e best of my knowledg	a				
	050 -		-	e best of my knowledge	•				
Approved	UEU 2	3 19 99		Operator Burlingto	n Resources				
	il Conservation Divi	sion	i	By Wan &	Pain				
ORIG	INAL SIGNED BY CH	LAPLIE T DERSON	.1		7				
Ву				Title Operations As	ssociate				
DEPUTY	OIL & GAS INSPEC	TOR, DIST. #3							

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Tes No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

Date Friday, December 03, 1999

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztee District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).