

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1850' FNL - 790' FWL
Sec. 11, T29N, R14W, NMPM

5. Lease Designation and Serial No.

SF 078110

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal I 1

9. API Well No.

30-045-08580

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged well as follows:

1. Ran tubing tag up @ 4801'. Amended procedure with approval of Wayne Townsend.
2. Spot 35 cu. ft. Class B cement w/2% CaCl₂ @ 4800'. Tag cement @ 4535'. Gallup plug 4535' - 4800'.
3. Spot 26 cu. ft. class "B" cement with 2% CaCl₂ at 3577' across Mesa Verde perforations. Mesa Verde plug 3390' - 3577'.
4. Spot 21 cu. ft. class "B" cement @ 2641'. Mesa Verde plug 2490' - 2641'.
5. Perforate 5 1/2" casing @ 1087'. Lower tubing to 1105'. Fill casing with 165 cu. ft. class "B" cement with 4% gel. POH with tubing. Fill casing with 39 cu. ft. class "B" w/4% gel w/ circulation out bradenhead. Closed bradenhead casing. Pump down bradenhead with 127 cu. ft. class "B" w/4% gel @ 650 psi. Surface plug 0' - 1087'.

Job complete 3-29-94.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander

Title Operations Manager

Date 3/31/94

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

APPROVED

APR 10 1994

DISTRICT MANAGER