

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. 1-89-IND-56	
2. NAME OF OPERATOR Continental Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo	
3. ADDRESS OF OPERATOR 152 North Durbin, Casper, Wyoming 82601		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL, 660' FEL (Unit Letter H)		8. FARM OR LEASE NAME Rattlesnake	
14. PERMIT NO.		9. WELL NO. 140	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5261' GLM		10. FIELD AND POOL, OR WILDCAT Rattlesnake - Penn. BCD	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 11, T29N, R19W	
		12. COUNTY OR PARISH San Juan	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Well History: TD 6733', PBTD 6433'. 13 3/8" surface casing, 9 5/8" intermediate casing, 36#, J-55 set at 4512' and 7" intermediate casing, 23#, J-55 set at 6532'. Perforated 6388'-6394', 6376'-6380' and 6356'-6359'. Well Status: Gas flowing.

We propose to plug the well as follows:

~~Set 20' sack cement plug from 6330' to 6430' KB.~~

~~Spot 25' plug in surface casing.~~

Set 10' length of 4" pipe in surface plug so that it projects at least 4' above ground level.

Top of 4" will be capped and a marker attached or welded on pipe.

200' cement plug 6230-6430'

150' " " 5375-5525'

100' " " 4275-4375

30' surface plug with marker.

USGS(6) NMOGCC(2) File(2)

18. I hereby certify that the foregoing is true and correct

SIGNED

Elmer L. Phillips

TITLE **Administrative Supervisor**

DATE

8-18-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

