e aperty a

A Care Same

HAUTER STATES

| DEPARTMENT OF THE INTERIOR | 5. LEASE 065557 A |
|--|---|
| GEOLOGICAL SURVEY | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different | 7. UNIT AGREEMENT NAME |
| reservoir, Use Form 9–331–C for such proposals.) | 8. FARM OR LEASE NAME Cornell |
| 1. oil gas double other 2. NAME OF OPERATOR | 9. WELL NO. (OWWO) |
| El Paso Natural Gas Company | 10. FIELD OR WILDCAT NAME Undes. Fruitland |
| 3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, NM 87401 | 11. SEC., T. R., M. OR BLK AND SURVEY OR AREA Sec. 1, T-29-N, K-12-W |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1850'N, 1850'E | NMPM |
| AT SURFACE: AT TOP PROD. INTERVAL: | 12. COUNTY OR PARISH San Juan New Mexico |
| AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, | 14. API NO. |
| REPORT, OR OTHER DATA | 15. ELEVATIONS (SHOW DF, KDB, AND WD) 5754' GL |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Plug Back SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: ABANDOR SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: ABANDOR SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: ABANDOR SUBSEQUENT REPORT OF: ABANDOR SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: ABANDOR S | (NOTE: Report results of multiple completion of the change on Form 9–330.) OCT 26 1981 CIL CON. COM. DIST. 3 |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner -22-81: MOL & RU. Ran 5 1/2" cmt Retainer on 2 3/8" Pic. Cliffs Zones w/71 cf. cmt. | irectionally drilled, give subsurface locations and not to this work.)* |
| 7-23-81: Pressure tested 5 1/2" casing to 1000#, ok. jts of 2 7/8", 6.4#, J-55 casing set at 1760' Basket set at 961'. Cmted w/ 165 cf. cmt. C 2 7/8 X 5 1/2 Annulus and squeeze cmted w/ 23 on the 5 1/2 X 7 7/8" Annulus to cover the 0 | . Baffle set at 1759'. Cmt. irc. to surface. Tied on to 0 cf. cmt. Circ. cmt. to surface |
| -24-81: Ran logs. Pressure tested 2 7/8" casing t from 1644' to 1664'. Fraced w/ 15,500# 10/20 gal. wtr. | sand, 16,930 gal. wtr. Flushed w/1400 |
| Subsurface Safety Valve: Manu. and Type | Set @ Ft. et at 1659'. |
| | erk October 16, 1981 |
| (This space for Federal or State of | fice use) |
| APPROVED BYTITLETITLE | DATE <u>(2.0.7778 %) (2.088</u> 0 |
| CONDITIONS OF ATTROVAL, II ANT. | GOT SO 1981 |
| | 1 9 t 6 a 1 301 |

*See Instructions on Reverse Side