

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

5-NMOCC
1-Christmann
1-Pruitt
1-Pan American
NEW MEXICO OIL CONSERVATION COMMISSION
1-Redfern Santa Fe, New Mexico
1-File

(Revised 7/1/60)
(Form C-100)

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE If State Land submit 6 Copies.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Redfern & Herd, Inc.

Pruitt

(Company or Operator)

(Lease)

Well No. 1, in SW 1/4 of NW 1/4, of Sec. 4, T. 29N, R. 13W, NMPM.

Basin-Dakota

Pool, San Juan

County.

Well is 1980 feet from North line and 1170 feet from West line

of Section 4. If State Land the Oil and Gas Lease No. is

Drilling Commenced 5-13, 1961 Drilling was Completed 5-27, 1961

Name of Drilling Contractor Exeter Drilling Co.

Address Farmington, N.M.

Elevation above sea level at Top of Tubing Head 5417 Gals. The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 5941 to 6021 (G) No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	24#	New	222.58	Tex Pattern			Surface
4-1/2	10.5#	New	6112.05	Guide		5941-6021	Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/4	8-5/8	235	140	Pump Plug		
7-7/8	4-1/2	6105	200	Pump Plug		

RECORD OF PRODUCTION AND STIMULATION


(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

250 Gal. M.S.A.; 80,000# 20-40; 111,370 water.

See C-103 for detailed frac information

Result of Production Stimulation

Depth Cleaned Out 6056



RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Tools were used from 0 feet to 6102 feet, and from feet to feet.
Tools were used from feet to feet, and from feet to feet.

PRODUCTION

Producing, 19.

LL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

LL: The production during the first 24 hours was 2500 M.C.F. plus Undetermined barrels of
liquid Hydrocarbon. Shut in Pressure 2050 lbs.

Time Shut in 7 days

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

	T. Devonian	T. Ojo Alamo
	T. Silurian	T. Kirtland-Fruitland
	T. Montoya	T. Farmington
	T. Simpson	T. Pictured Cliffs
ers	T. McKee	T. Menefee
n	T. Ellenburger	T. Point Lookout
burg	T. Gr. Wash	T. Mancos
Andres	T. Granite	T. Dakota
cta	T.	T. Morrison
card	T.	T. Penn
is	T.	T.
	T.	T.
	T.	T.
	T.	T.

FORMATION RECORD

To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
						Log Turn
						Pictured Cliffs 1260
						Lords 1453
						Cliffhouse 2783
						Menefee 2925
						Point Lookout 3786
						Mancos 4020
						Gallup 4975
						Greenhorn 5740
						Graneros Shale 5790
						Graneros Sand 5840
						Dakota 5937

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far determined from available records.

Operator Redfern & Herd, Inc.
Original signed by T. A. Dugan
September 27, 1961
Address 1007 N. Dustin, Farmington, N.M.
Position as Title Engineer