

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Dual Completion	X

May 9, 1961

Albuquerque, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the.....

Pubco Petroleum Corporation
Company or Operator

Federal
Lease

Well No. **6-B**

in the

NW/4, NE/4

of Sec. **6**

T. **29N**

R. **11W**

N. M. P. M.,

Basin Dakota - Blanco MW Pool

San Juan

County.

The dates of this work were as follows: **May 1-7, 1961**


9-331A

Notice of intention to do the work was ~~(was not)~~ submitted on Form **C-102** on **4-21-61**, 19.....

and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Moved in Jim Lawrence Gas Rotary 5-1-61. Killed Dakota w/water. Pulled tubing. Ran Baker Model "D" production packer with pushout plug to 6404. Perf. 4 bullets/ft 3805 and 3495. Set Baker magnesium retainer at 3787, broke circ. down tubing thru 3805 and back to 3495 and out annulus. Cemented with 100 sax reg. Squeezed perfs at 3495 w/100 sax to 2500#. Squeezed perfs at 3805 twice 100 sax reg plus 50 sax Latex to 2700#. Perf. 3695-3710. Ran 2" EUE tubing and stung in to Baker Model D Packer. Cliffhouse came in natural after perf. for a wet gauge of 9,304 MCFD. Rocked Cliffhouse into Dakota and brought Dakota in. Workover completed 5 PM 5-7-61.



Witnessed by **N. E. Maxwell, Jr.**

Name

Pubco Petroleum Corporation

Company

Manager, Prod. Dept.

Title

APPROVED:

OIL CONSERVATION COMMISSION

Original Signed Emery C. Arnold

Name

Supervisor Dist. # 3

Title

MAY 10 1961

Date

I hereby swear or affirm that the information given above is true and correct.

N. E. Maxwell, Jr.

Name

N. E. Maxwell, Jr.

Position **Manager, Production Department**

Representing **Pubco Petroleum Corporation**
Company or Operator

Address **Box 1419, Albuquerque, New Mexico**