Form 3160-5 (June 1990)

## UNITED STATES

FORM APPROVED Budget Bureau No. 1004-0135

DEPARTMENT OF THE INTERIOR Expires: March 31, 1993 **BUREAU OF LAND MANAGEMENT** 5. LEASE DESIGNATION AND SERIAL NO. NM021118 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS,  $\frac{1}{100}$   $\frac{1}{100}$   $\frac{1}{100}$ Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. IF UNIT OR CA, AGREEMENT DESIGNATION SUBMIT IN TRIPLICATE 8910069600 1. TYPE OF WELL 8. WELL NAME AND NO. GAS WELL OIL WELL OTHER : FEDERAL #5 NAME OF OPERATOR 9. API WELL NO. CONOCO INC. 30-045-08852 ADDRESS AND TELEPHONE NO. 10. FIELD AND POOL, OR EXPLORATORY AREA 10 DESTA DR., SUITE 100W, MIDLAND, TX 79705-4500 (915)686-5424 BASIN DAKOTA LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description) 11. COUNTY OR PARISH, STATE 890' FNL AND 1800' FEL, SECTO5, T29N, R12W, UNIT LTR 'B2' SAN JUAN, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Plugging Back Non-Routine Fracturing Final Abandonment Notice Casing Repair Water Shut-Off Altering Casing Conversion to Injection Other: SLIMHOLE W/ 4-1/2" CSG Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 2-4-97 MIRU. PU AND RIH W/ 2-3/8" TBG AND HBTON BAILER, TAG FILL 6030', CO W/ BAILER TO 6208', POOH W/ TOOLS. RIH W/ MULESHOE ON 2-3/8" TO 6184', ATTEMPT TO CIRC, PU 900' DROP 3 SXS 20/40 SAND, DISPLACE W/ 12 BBLS KCL, WAIT 1-1/2" HRS, RIH TAG SAND, NO-SAND TO 6207', POOH W/TBG, RIH W/SWAGE TOOLS TO 6185' - OK, NO TIGHT SPOTS, POOH, RIH W/ WIRELINE GR AND JUNK BASKET TO 5750' AND COULD NOT GET DOWN, POOH, RIH W/ SINKER BAR AND TAG FILL 6207', POOH, RIH W/ WIRELINE DUMP BAILER, SPOT 3 SXS SAND IN 3 RUNS TAG SAND AT 6180', RD WIRELINE, FOUND TBG HEAD WELDED TO BRADENHEAD, RU FOR 4-1/2" PIPE, RIH W/ 4-1/2" JT W/ FLOAT SHOE AND JTS OF 4-1/2" WOOLEY FLUSH JT CSG, 135 JTS, TO 5786', CIRC HOLE W/ WATER 1.5 - 2.0 BPM AT 730# LEAD IN W/ 2000 GAL PKR FLUID W/ FL-62 LAST 210 GALS W/ RED DYE, PUMP 35 BBLS 12# CMT W/ ♣ ADDITIVES, TAIL IN W/ 2 SXS CLASS B, DISPLACE W/ 90.5 BBLS WATER AT 1 BPM, RECIP 10-12', DID NOT BUMP PLUG, SHUT IN W/ 1100#, BLED OFF 0#, SHUT IN, TEST SEAL IN CSG HEAD AFTER SILICON PEPACK TO 1000# - OK, RIH W/ 3-7/8" BIT AND 2-3/8" TBG TAG WIPER PLUG AT 5725', DO CMT AND SHOE, CO TO 5903', PU TO 5840' CIRC CLEAN, TAG FILL AT 5903', CO TO 6190', DO FILL TO 6310', STARTED TO LOSE CIRC UNTIL INTO LOWER DK PERFS, 6344', CO W/ N2 TO 6411', CIRC HOLE CLEAN, LEAVES 68' RATHOLE BELOW PERFS, POOH W/ TBG AND BIT, TIH W/ SN AND 199 JTS 2-3/8" J-55 8RD 4.7# TBG AND LAND AT 6284' KB, RU TO SWAB, NO FLOW, SPOT 12 BBLS 15% HCL DISPLACE W/ 12 BBLS 1% KCL, TOTAL TBG VOLUME 24 BBLS WELL ON VACUUM FOLLOWING ACID SPOT, WAIT 1-1/2 HRS, SWAB, KICK OFF WELL. circulated due theo x 1.0 bbl ent. to surpre 2-20-97 14. I hereby certify that the foregoing is true and correct Web Beminds fatitle AGENT FOR CONOCO INC. (This space for Federal or State office use) APPROVED BY TITLE Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of ARMANGTON DESTRI fictitious or fraudulent statements or representations as to any matter within its jurisdiction. NMOCD