



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 078615

Unit Northeast Blanco

Unit Agreement No. 1, Sec. 989

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELL February 25 1958

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REPAIR REPAIR WELL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 24, 1958

Well No. Howell 1-0 is located 1090 ft. from N line and 1550 ft. from W line of sec. 24

34/4 Sec. 24 30N 8W 104PM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesaverde San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6196 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Pull 2-3/8" tubing, clean out with gas to approximately 5357', run approximately 700' 5-1/2" liner (with turned down collars), and cement with 200 sacks regular cement.

Selectively perforate the Mesaverde Groups and Sand Water Frac in two stages with 50,000 gallons of water and 50,000 lbs. of sand per stage.

Rerun tubing and repotential.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blackwood & Nichols Company

Address P. O. Box 1237

Durango, Colorado

Original Signed
by DeLasso Loos

Title Field Superintendent