m 9- eb. 19	881 a 61)		
	m 9-	m 9-381a reb. 1961)	m 9-381 a reb. 1981)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

		-	
Land Of	fice	iente fo	
Lease No	D	078578	
		Section	

SUNDRY NOTICES AND REPORTS ON WELLS

DOME -	
NOTICE OF INTENTION TO RE-DRILL ON REAL NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF REMILENS OR REPAIR. SUBSEQUENT REPORT OF ABANDONMENT. SUPPLEMENTARY WELL HISTORY.
(INDICATE ABOVE BY CHECK MAR	K NATURE OF REPORT, NOTICE, OR OTHER DATA)

			August 3	8	19
Florence WILL 60 is locate	ed 1650 ft. from	n. Neline and	1825 ft. from	E line of second	
Well No is locate			No. Prof.	" / MLUL	IVFN
HE/4 Section 21	T-30-A	(Range)	(Meridian)	- I see	TU
(14 Sec. and Sec. No.)	(Twp.)	a Juan	(8)	tate or Tentifory)	1962
(Field)		y or Subdivision)		/ CON	COM.
The elevation of the derrick	floor above sea l	evel is 5818	ft. ¥•፣•		3 /
The old was	DET	AILS OF WOR	K	u	. coment-

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Killed well w/water. Pulled 136 jts. 1.8" tubing. Set retrievable bridge pluc at 3008'. Preserved caming to 900 pei. Non temperature survey from 3000'. Anomalies at 1580' and 1550'. Perference 7" essing w/4 holes at 2550'. Set retrievable perfor at 2429'. Proke circulation with water through perforations at 2550. Comented through perforations in 7" casing w/1030 sacks Incor coment 6/41 cel and 11 CaCl: Temperature survey indicates top coment at 655', Drilled out cament in easing. Tested to 1808 pei. Resevered retrievable bridge plug. Ren 130 jto. 2-3/8" tubing to 4317". Placed well on production.

I understand ti	Delhi-Taylor Gil Corporation	se Geological Survey before operations may be commenced.
mpany	. O. Drewer 1198	Original signed
	armington, New Munico	By E. W. Guynn By District Engineer Title