

TENNECO OIL COMPANY

Printed in USA

☐ DEV. DRLG.☐ P & A☐ WC DRLG.☐ CONST.

DRILLING RECORD

AFE NO. _____

☐ RECOMPLETION ☐

FIELD _____

Blanco Mesa Verde

LEASE Linda Nye

WELL NO. 1

DATE	DEPTH	PAGE 3	DETAIL OF OPERATION
11-23	(con't)		at 5" x 7" annulus would come and go. Displ. cmt w/75 BW.
			Bumped plug with 2200#, held 5 minutes OK. Float held OK. WOC
			4:00 PM, braden head flowing gas and black wtr at end of job. Picked
			up BOPE, hung casing, cut off installed rector weld ring and slips
			Nippled up tubing head. Changed rams. SDON DC \$11,473 TC \$14,473
11-24	PBTD 4838		Picked up 3 7/8" WO bit on 2- 3-1/8" drill collars. Ran to 3979'
			Hit soft fill. Drld top plug and baffel at 3990'. Drld cmt to
			4021'. Pump press 100-110 psi. 28 SPM 62 GPM. nmt cuttings
			good. Drld pkr shoe at 4021'. Pressure tested 5 5" x 7" annulus
			to 500 psi for 5 minutes. Held good DC \$800 TC \$15,373
11-25	PBTD 4838		Ran bit and 2 drill collars to B.P. at 4150'. Tagged up. Shut rams.
			Plugged tubing. Pressured csg to 750 psi for 15 minutes. No bleed
			off. Drld B.P. to 4151' - lost returns. Hole went on strong vacuum
			Couldn't dislodge B.P. Pulled tubing, drill collars and bit. Ran
			Baker sandline drill-pushed & drld plug from 4150' to 4809' in two runs.
			Pulled sandline drill. Had portion of slips and fine fill in sandline
			drill each run. SDON DC \$1000 nC \$16,373
11-26	PBTD 4838		Ran 156 joints of 2-3/8" 47# J-55 EUE 8-RD used tubing as follwos:
			KB to top of 2-1/2" tbg hanger and swage 5.00
			155 jts as above 4739.20
			1 - Baker "F" nipple 1.81" x 2-3/8" 1.50
			1 - joint as above 28.50