

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.**Santa Fe 079511**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)7. UNIT AGREEMENT NAME
**N E Blanco Unit Agmt.
No. 1, Sec. 929**

8. FARM OR LEASE NAME

Northeast Blanco Unit

9. WELL NO.

SX

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**SW/4 Sec. 13-30N-8W NMPM**

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico1. OIL ☐ GAS ☒ OTHER ☐

2. NAME OF OPERATOR

BLACKWOOD & NICHOLS COMPANY

3. ADDRESS OF OPERATOR

P.O. BOX 1237, DURANGO, COLORADO 813014. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface**1190' F/SL - 1100' F/WL**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6099' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☒ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-27-74 Pulled 2 3/8" tubing, set retrievable bridge at 4684' in 5" casing. Ran test packer and found holes in 5" casing 385' to 1488'. Set retrievable packer at 232'. Squeeze cemented with 450 sacks class B cement with 2% calcium chloride and .075% Hald 9. Final pressure 250 P.S.I.

1-30-74 Drilled cement to 1150', found small holes in 5" casing 520' to 1150', could not pump in below 1500 PSI. Ran 2 3/8" tubing open ended, circulated 100 sacks Class B cement, with 2% calcium chloride and .075% Hald 9, to surface. Came out of hole with tubing, pumped cement through Bradenhead at 1500 PSI to 250'.

2-3-74 Drilled cement, tested 5" casing with 1500 PSI, held OK.

2-5-74 Cleaned out 2 7/8" liner to 5290'.

2-6-74 Ran 147 Jts. 2 3/8", 4.7# EUE tubing 4650' with production packer **FE at 4660'.**
bottom of tubing set 4711'.



18. I hereby certify that the foregoing is true and correct

SIGNED by DeLasso Loos

DeLasso LoosTITLE **Field Superintendent**DATE **2-11-74**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FEB 13 1974

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

Instructions

General: This form is designed for use in submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, whether are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of separating of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

GPO 8 37-499

967-851