

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

January 21, 1953

Farmington, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

El Paso Natural Gas Company

Menos Pool Unit

(Company or Operator)

(Lease)

Pioneer Well Service

Well No. 1 in the SW 1/4 of Sec. 11

(Contractor)

T. 30N, R. 8W, NMPM, Blanco Pool, San Juan County.

The Dates of this work were as follows: January 16, 1953

Notice of intention to do the work (was) submitted on Form C-102 on December 19, 1952

(Cross out incorrect words)

and approval of the proposed plan (was) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Spudded well January 2, 1953. Total depth 128'.
 On January 3, 1953, ran 3 joints 9-5/8" surface casing set at 128' with 120 sacks regular cement circulated to surface.
 January 10, 1953, total depth 975'. Surface cement broke down and started making water on outside of casing. Re cemented casing with 150 sacks regular cement and two sacks Calcium Chloride circulated to surface.
 January 12, 1953, total depth 978'. Well started making water on outside of casing. Re cemented surface with 200 sacks regular cement and two sacks Calcium Chloride circulated to surface.
 January 14, 1953, total depth 978'. Surface casing gave way, pulled three joints of surface casing, reamed hole 18-3/4" to 291'.
 January 16, 1953, total depth 978'. Ran seven joints 9-5/8" surface casing (280') set at 291' with 300 sacks quick strength cement circulated to surface.

Witnessed by Dale Lockett (Name)

El Paso Natural Gas Company (Company)

Petroleum Engineer (Title)

Approved: OIL CONSERVATION COMMISSION

Emery C. Gould (Name)

(Title)


I hereby certify that the information given above is true and complete to the best of my knowledge

Name: D. E. Lockett

Position: Petroleum Engineer

Representing: El Paso Natural Gas Company

Address: Box 997, Farmington, New Mexico



1-23-53 (Date)