

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator PURCO PETROLEUM CORP.		5. State Oil & Gas Lease No. B-10603
3. Address of Operator P.O. Box 7, Artec, New Mexico		7. Unit Agreement Name
4. Location of Well UNIT LETTER A 990 FEET FROM THE North LINE AND 990 FEET FROM THE East LINE, SECTION 2 TOWNSHIP 30 North RANGE 8 West NMPM.		8. Farm or Lease Name State
15. Elevation (Show whether DF, RT, GR, etc.) 6397 Gr.		9. Well No. 19
		10. Field and Pool, or Wildcat Blanco Mesaverde
		12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-27-65

Moved in rig; could not pull tbg.; cut tbg. at 5210' and pulled.
 Ran corrosion log in 5 1/2" csg; csg. OK.
 Set cement retainer at 5090'; squeezed open hole w/100 sax regular cnt., cut 5 1/2" csg off at 4200'; pulled 5 1/2" and laid down.
 Set cnt. retainer at 3530' in 7" csg.; squeezed open hole w/260 sax Class C, 8% gal, 12 1/4 gilsonite/sk, and 100 sax regular w/2 1/2 CaCl and 15% sand.
 Pressure tested 7" csg. to 1500 psi; test OK.
 Perforated 7" csg. at 2775'; set cement retainer at 2619' and squeezed 7" w/200 sax Class C, 2 1/2 CaCl. WOB 24 hours. Top of Fruitland at 2977'.
 Preparing to drill directional hole from base of 7" csg. at 3628' through Mesaverde and run full string of 4 1/2" csg. cemented to surface.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles E. Ramsey

TITLE Petroleum Engineer

DATE 4-2-65

Original Signed Emery C. Arnold

APPROVED BY _____

TITLE Supervisor Dist. # 3

DATE APR 5 1965

CONDITIONS OF APPROVAL, IF ANY: