Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
SF 080247-A

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals


6. If Indian, Allottee or Tribe Name N/A

SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation N/A
1. Type of Well Oil Well Swell Other 2. Name of Operator	8. Well Name and No. Simmons #8
D.J. Simmons Company 3. Address and Telephone No. P O Box 1409 Farmington NM 87499	9. API Well No. 30045-11866-0051 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1700' FNL & 1730 FEL Sec. 25 T29N R9W	Blanco - PC 11. County or Parish, State San Juan, NM
CHECK APPROPRIATE BOY(s) TO INDICATE MATURE OF NOTICE RE	

12.	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
****	TYPE OF SUBMISSION	TYPE OF ACTION		
• • • • • • • • • • • • • • • • • • • •	Notice of Intent	X Abandonment	Change of Plans	
	Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing	
	Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off Conversion to Injection	
	production Proved Non-	Commercial	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran CBL & had good Cmt. up to 1482' RIH w/ retainer and set @ 2358' Cmt. PC w/ 25 SX class B. Set plugs as follows; 1st 10 Sx. 2263'-2149', pumped mud 2149' to 1573; 2nd plug 100 Sx. from 1573' - 787'; Pump mud from 787' to 200'. Perforate squeeze hole @ 200' and cementw/ 112 Sx. class B neat, circulated 3 Bbls of cement to surface ND BOP'S, Cut off wellheads & Install dry hole marker.



OIL CON. DIV.

14. I hereby certify that the foregoing is true and correct Signed Robert Robe	Engineering _{Tide} Consultant	Daic 12/07/92	
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title	APPROVED	_

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States of the United