


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Santa Fe  
Lease No. 070197  
Unit W/2

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 22, 1961, 19

Turner - Eye

Well No. 8-1 is located 1,450 ft. from S line and 750 ft. from E line of sec. 8

1/4 Section 8

(1/4 Sec. and Sec. No.)

T 39-N

(Twp.)

R 10-W

(Range)

N.M.P.M.

(Meridian)

Basin Dakota

(Field)

San Juan County

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 5,901 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1/3/61. After drilling to 5720' M.B., run 121 joints (5732') of 5-1/2" OD 13.5# casing to 5718'. Cemented 1st stage with 175 sacks 30/50 Minn. Cement. Baker stage tool - set at 4753'. Cemented 2nd stage with 135 sacks neat cement plus 303 cubic feet of Biocel D., followed by 64 sacks neat cement plus 64 sacks Biocel A plus 84 gal plus 12 1/2 lbs Silicate per sack. Had some lost circulation during latter part of cementing.

1/3/61. After moving in completion tools, tested casing to 5000'. Held O.K. Spotted 500 gals 15% MCA. Per forecast 4 shots per foot: 6643-60', 6623-32', 6603-24', 6571-74', 6492-6522'. Sand water fraced using 60, 325 hundred gallons water 1% calcium chloride, 10% GWT per 1,000 gal., 10% wt. 4 per 1 M gal., 1 gal. Hyle per 1 M gal. and 80,000# 20/40 sand. Dropped 90 balls after 40,000# sand and 50 after 45,000#. No apparent reaction to balls. Avg. inj. 57.4 GPM. On 1/10 run 211 joints 2-3/8" OD M.B., 1 -4' sub, 1 -2' sub, total string 6647' - landed at 6697' M.B. Shut well in on 1/16/60 to await potential test and pipe line connection.

Company J. Glenn TurnerAddress Box 726Farmington, New MexicoBy C. Deason Neal, Agent in Farmington  
Title \_\_\_\_\_