STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Location of Well: Unit A Sec. 13	Tree 29			Well No. 1		
	Twp	Rge	10	Cou	inty	SAN JUAN
NAME OF RESE	TYPE OF F	I t	METHOD OF PROD. (Flow or Art. Lift)		PROD. MEDIUM (Tbg. or Cag.)	
Upper Completion MESAVERDE	GA	ıs	FLOW		TUBING	
Completion DAKOTA	GA	GAS		FLOW TUBI		
	PRE-FL	OW SHUT-IN P	RESSURE DATA			
Upper Hour, date shut-in	ut-in	i i			Stabilized? (Yes or No)	
Completion 11-30-86 3 DAYS Hour, date snut-in Length of time snut-in			550			
Hour, date shut-in Length of time shut-in III-30-86 I DAYS		yt-in	Stabilized? (Yes)			Yes or No)
		FLOW TEST	NO. 1			
Commenced at (hour, date)* 12-03		Zone producing (Upper or Lawer): LUWER				
TIME LAPSED TIME (hour, clate) SINCE*	PRES Upper Completion	SURE Lower Completion	PROD. ZONE TEMP.	REMARKS		ARKS
12-01 1 DAY	550	550		BOTH ZONES SHUT-IN		
12-02 2 DAYS	550	550		BOTH ZONES SHUT-IN		
12-03 3 DAYS	550	553		BOTH ZONES SHUT-IN		
12-04 1 DAY	475	277		LOWER ZONE FLOWING		
12-05 2 DAYS	516	451		LOPER ZO	NE FLOW	IING
		S.o.	4 1 0 1086	is an area		
roduction rate during test Dil:BC	PD based on	C Bbls. in	S Siours	G	rav	GOR
Fas: 843	MCFF	PD: Tested thru	(Orifice or Meter): METER		·
		ST SHUT-IN PR				
Upper Hour, date snut-in Langth of time snut-in mpletion			· · · · · · · · · · · · · · · · · · ·		Stabilized? Yes or No.	
Lower Hour, date shut-in Length of time shut-in maletion		-ın	SI press. psig	Dailg Stabilized? (Yes or No)		es or No)

FLOW TEST NO. 2

Zone producing (Upper or Lower):

TIME (hour, date)	LAPSED TIME	PRESSURE		PROD. ZONE	
	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS
					
1					
· •					
	<u> </u>		1	1	
Production rate of	during test				
Oil:	ВОР	D based on	Bbls. in	Hours.	Grav GOR
G2s:		MCI	PD: Tested thru	(Orifice or Meter):
Remarks:					
					·
I hereby certify t	hat the informati	ion herein contain	ed is true and co	emplete to the bes	τ of my knowledge.
Approved			10 (Operator SOUT	HLAND ROYALTY COMPANY
	Oil Conservation I			Sperator /	111
			H	By While	Melah
Rv			7	ricie PROD	UCTION ENGINEER
<u> </u>	······································	· · · · · · · · · · · · · · · · · · ·			8 1988
Tirle			T	Jare (17.1)	$oldsymbol{G} = \{ i_1, i_2, \dots, i_n \}$

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) **

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shur-in for pressure stabilization. Both zones shall remain shur-in until the well-head pressure in each has stabilized, provided however, that they need not remain shur-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accor-

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously snown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing