

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SW 078926

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER

Water Injection Well

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 480, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1830' FSL & 790' FSL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5889' RDS

7. UNIT AGREEMENT NAME

Gallegos Canyon Unit

8. FARM OR LEASE NAME

9. WELL NO.

92

10. FIELD AND POOL, OR WILDCAT

Tatch Gulch

11. SEC. T., R., M., OR BLM. AND
SURVEY OR AREA

**SW 1/4 NW 1/4 Section 13
T-28N, R-13W**

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Referring to our Form 9-331 of 4-18-66, Gallegos Canyon Unit Well No. 92 was plugged and abandoned 4-19-66 as follows:

1. Spensed 40 sacks cement (containing 6% Gel and 2% calcium chloride) into casing perforations 5720-28' (packer set at 5661').
2. Loaded hole with fluid and spotted 75 sacks cement (6% Gel and 2% calcium chloride) to 3150'.
3. Loaded hole with fluid and spotted 10 sacks cement (6% Gel and 2% calcium chloride) from 1500' to 1400'.
4. Loaded hole with fluid and spotted 5 sacks (6% Gel and 2% calcium chloride) from 50' to surface.
5. Pumped 75 sacks cement (6% Gel and 2% calcium chloride) into 2-1/2" x 4-1/2" casing annulus.
6. Cut off wellhead, erected PMA marker, and cleaned up location.

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNATURE

SIGNED

G. W. Eason, Jr.

TITLE

Area Engineer


(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations of Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1961-O-465229

687-351

SUMMARY NOTICES AND REPORTS ON WELLS

THIS SUMMARY NOTICE IS TO BE FILLED IN BY THE OPERATOR OF THE WELL. IT IS TO BE SUBMITTED TO THE GEOLOGICAL SURVEY, WASHINGTON, D.C. 20548, WITH THE APPLICATION FOR PERMIT TO DRILL OR TO ABANDON A WELL.

NAME OF OPERATOR

NAME OF OPERATOR

NAME OF OPERATOR

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition

1961, 2nd Edition