

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency

Navajo Tribal

Allottee

Lease No. 14-20-603-2193

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Navajo Tribal "H"


Farmington, New Mexico November 7, 1962

Well No. 7 is located 2130 ft. from S line and 510 ft. from E line of sec. 24

NE 1/4 SE 1/4 Section 24 T-29-N R-11-W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Tetah Gallup San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5459 ft. (RDB)



DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

In an effort to increase oil production, we propose to re-stimulate the Navajo Tribal "H" No. 7 as follows:

1. Set retrievable bridge plug at about 5210 and pressure test casing.
2. Run correlation log and perforate upper Gallup zone with 6 JSPT from 5181-5186.
3. Frac with 20,000 gal. crude oil containing 90 lbs. Adomite Mark II fluid loss additive per 1,000 gal. and 5 gal. G-15 partial gelling effect and friction loss control per 1,000 gals. with 15,000 lbs. 20-40 mesh sand with tail in of 5,000 lb. 10-20 mesh sand.
4. Stabilize pressure, clean out sand, pull bridge plug and swab in well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 480

Farmington, New Mexico

Attn: L. O. Speer, Jr.

By ORIGINAL SIGNED BY
F. H. ROLLINGSWORTH

Title Petroleum Engineer

Verbal permission received
11-7-62 Baier to Rollingsworth