Form (A)	n 9- 8 pril 19	331 b 52)	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency	NAVAJO		
WINDOW			
Allottee			
	119-Ind.872		

and the second s	i	CHARTON TO	DODE OF WATER CHIEF OF	4 1 1 1 121 1
NOTICE OF INTENTION TO DRILL		11	PORT OF WATER SHUT-OFF PORT OF SHOOTING OR ACIDIZ	J. (* 1.) 1
NOTICE OF INTENTION TO CHANG		CURCEOUENT DE	PORT OF ALTERING CASING	
NOTICE OF INTENTION TO TEST V NOTICE OF INTENTION TO REDRI		SUBSPOUENT RE		S GEOLOGICAL STA
NOTICE OF INTENTION TO SHOOT		SUBSPONENT RE	PORT OF ABANDONMENT.	EN TEN TEN TEN
NOTICE OF INTENTION TO PULL	l l	1	WELL HISTORY	X
NOTICE OF INTENTION TO ABANE	. 1			
(IND	NCATE ABOVE BY CHECK MARK N.	ATURE OF REPORT, N		
		y	January 23	, 19 <u>61</u>
Gulf-Nevajo	- 000	(N)	220	. 22
ell Nois	located 990 ft. from	n line and	tt. from $\{\overline{\mathbb{W}}\}$ lin	ne of sec
(% Sec. and Sec. No.)	29X (Twp.)	17W (Range)	(Meridian)	
(4 sec. and sec. No.)	San Juan Cou		New Mexi	co ·
Wilder (Field)		Subdivision)	(State or To	
tate names of and expected dept	ths to objective sands; show size ing points, and all ot	s, weights, and lengt her important prop	hs of proposed casings; indicate used work)	mudding jobs, comence
Spudded 1/10	/61. Drilled 8 3/	/h" hole to rilled h 3/h	52'. Set 7 5/8"	casing Ran
Spudded 1/10 at 52' with 50 se Schlumberger Elec at 1090'. Set 12	/61. Drilled 8 3/ loke of cement. Dr tric log from 564 cement plug	/h" hole to rilled h 3/h to 1123'. at 90'. Se	52'. Set 7 5/8" " hole to 1124'. Set 20 sacks desc	casing Ran at plug
Spudded 1/10 at 52' with 50 se Schlumberger Elec at 1090'. Set 12)/61. Drilled 8 3/ loke of cement. Dr dric log from 564	/h" hole to rilled h 3/h to 1123'. at 90'. Se	52'. Set 7 5/8" " hole to 1124'. Set 20 sacks desc	casing Ran at plug
Spudded 1/10 at 52' with 50 se Schlumberger Elec at 1090'. Set 12	/61. Drilled 8 3/ loke of cement. Dr tric log from 564 cement plug	/h" hole to rilled h 3/h to 1123'. at 90'. Se	52'. Set 7 5/8" " hole to 1124'. Set 20 sacks desc	casing Ran at plug
Spudded 1/10 at 52' with 50 se Schlumberger Elec at 1090'. Set 12	/61. Drilled 8 3/ loke of cement. Dr tric log from 564 cement plug	/h" hole to rilled h 3/h to 1123'. at 90'. Se	52'. Set 7 5/8" " hole to 1124'. Set 20 sacks cene et dry hole marker	casing Ran at plug
Spudded 1/10 at 52' with 50 se Schlumberger Elec at 1090'. Set 12	/61. Drilled 8 3/ loke of cement. Dr tric log from 564 cement plug	/h" hole to rilled h 3/h to 1123'. at 90'. Se	52'. Set 7 5/8" " hole to 1124'. Set 20 sacks desc	casing Ran at plug
Spudded 1/10 at 52' with 50 se Schlumberger Elec at 1090'. Set 12 surface with 5 se	/61. Drilled 8 3/10ks of cement. Driver log from 564 sack cement plug loks. P. & A. 1/2/	/li" hole to rilled i 3/i to 1123'. at 90'. Se 2/61	52'. Set 7 5/8" i" hole to 112h'. Set 20 sacks cene it dry hole marker AN 24 196 CON. CO	casing Ran at plug at
at 52' with 50 se Schlumberger Elec at 1090'. Set 12 surface with 5 se I understand that this plan of	/61. Drilled 8 3/10ks of cement. Driving log from 56% sack cement plug toks. P. & A. 1/2/2	/li" hole to rilled i 3/i to 1123'. at 90'. Se 2/61	52'. Set 7 5/8" i" hole to 112h'. Set 20 sacks cene it dry hole marker AN 24 196 CON. CO	casing Ran at plug at
Spudded 1/10 at 52' with 50 se Schlumberger Elect at 1090'. Set 12 surface with 5 se I understand that this plan of Company J. K. We	/61. Drilled 8 3/ loke of cement. Driving log from 564 sack cement plug loke. P. & A. 1/22 work must receive approval in adley	/li" hole to rilled i 3/i to 1123'. at 90'. Se 2/61	52'. Set 7 5/8" i" hole to 112h'. Set 20 sacks cene it dry hole marker AN 24 196 CON. CO	casing Ran at plug at
Spudded 1/10 at 52' with 50 se Schlumberger Elect at 1090'. Set 12 surface with 5 se I understand that this plan of Company J. K. We	/61. Drilled 8 3/ loke of cement. Driving log from 564 sack cement plug loke. P. & A. 1/22 work must receive approval in adley	/li" hole to rilled i 3/i to 1123'. at 90'. Se 2/61	52'. Set 7 5/8" i" hole to 112h'. Set 20 sacks cene it dry hole marker AN 24 196 CON. CO	casing Ran at plug at
Spudded 1/10 at 52' with 50 se Schlumberger Elect at 1090'. Set 12 surface with 5 se I understand that this plan of Company J. K. We	/61. Drilled 8 3/ loke of cement. Driving log from 564 sack cement plug loke. P. & A. 1/22 work must receive approval in adley	/li" hole to rilled i 3/i to 1123'. at 90'. Se 2/61	52'. Set 7 5/8" i" hole to 112h'. Set 20 sacks cene it dry hole marker AN 24 196 CON. CO	casing Ran at plug at

U. S. GOVERNMENT PRINT

U. S. GOVERNMENT PRINTING OFFICE 16-8437b-8

in the consistency of the control of the term of the control of th