



(SUBMIT IN TRIPLICATE)
**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

Budget Bureau No. 42-10559.1
Approval expires 12-31-60.
Indian Agency Navajo
Window Rock
Allottee 14-20-603-1252
Lease No. _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
FEB 9 1961
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

Well No. 1 is located 990 ft. from N line and 330 ft. from W line of sec. 22
NE 1/4 22 (1/4 Sec. and Sec. No.) 29N (Twp.) 17W (Range) H.M.P.M. (Meridian)
Wildcat (Field) San Juan County (County or Subdivision) New Mexico (State or Territory)
The elevation of the derrick floor above sea level is 5105 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 1-10-61. Drilled 8-3/4" hole to 52'. Set 7-5/8" casing at 52' with 50 sacks of cement. Drilled 4-3/4" hole to 1124'. Ran Schlumberger Electric Log from 56' to 1123'.
Propose to set 20 sack cement plug at 1090' and 12 sack cement plug at 90' and 5 sack cement plug at surface. This will be final abandonment.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company J. K. Madley
Address Tombigbee, Arkansas

By Harrell Budd
Harrell Budd
Title Consulting Geologist

