

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 2, 1955
(Date)Durango, Colorado
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Blackwood & Nichols Co.

(Company or Operator)

Southeast Elanco Unit

(Lease)

Fletcher-Soley Drilling Co.

(Contractor)

Well No. 27-13 in the NE 1/4 SE 1/4 of Sec. 13

T. 30 N., R. 8 W., NMPM., Elanco Mesquite Pool, San Juan County.

The Dates of this work were as follows: April 28 - May 17, 1955

Notice of intention to do the work (was) ~~shown~~ submitted on Form C-102 on April 5, 1955
(Cross out incorrect words)and approval of the proposed plan (was) ~~shown~~ obtained. April 28, 1955

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Spudded at 5:00 AM 4-28-55.

On 4-30-55 ran 6 7/8 10-3/4" 32.750 ETC Casing - 145' set at 175'. Cemented with 225 sacks Ideal regular cement. Cement circulated. Tested 10-3/4" casing with 800 PSI for 15 minutes before and after drilling cement and plug. Held OK.

On 5-11-55 Ran 106 7/8 7-5/8" 26.400 ETC Casing - 3039' set at 3090'. Cemented with 225 sacks 1:1 mixture of cement and pozzol with 46 gal and 1/20 floccs per sack. Top of cement at 2940'. Tested 7-5/8" casing with 800 PSI for 15 minutes. Held OK. Drilled with gas to 3030'.

On 5-17-55 ran 138 7/8 5-1/2" 15.500 ETC Casing - 3039' set at 3049'. Cemented with 125 sacks 46 gal. Top of cement at 3110'. Tested 5-1/2" casing with 800 PSI for 30 minutes. Held OK. Drilled to 3140' to sandface.

Witnessed by Delancee Loos (Name) Blackwood & Nichols Co. (Company) Field Superintendent (Title)

Approved:

OIL CONSERVATION COMMISSION

Original Signed Emory C. Arnold

(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge

Name Delancee Loos Delancee LoosPosition Field SuperintendentRepresenting Blackwood & Nichols Co.Address P.O. Box 1277, Durango, Colo.

Oil and Gas Inspector Dist. #3.

(Title)

JUN 7 1955

(Date)

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received <u>5</u>		
DISTRIBUTION		
	NO. FURNISHED	
Operator		
Santa Fe	1	
Proration Office		
State Land Office		
U. S. G. S.		
Transporter		
File	1	✓