

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Blackwood & Nichols Co., Ltd.
3. ADDRESS OF OPERATOR
P. O. Box 1237, Durango, Colorado 81301
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' F/SL - 1080' F/WL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
SF 079042
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME NEBU Agreement No. 1, Sec. 929
8. FARM OR LEASE NAME
Northeast Blanco Unit
9. WELL NO.
3X
10. FIELD OR WILDCAT NAME
Blanco Mesaverde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
L-5-30N-7W
12. COUNTY OR PARISH San Juan 13. STATE New Mexico
14. API NO.
30-039-007910
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6233' KB

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☒
- (other)

SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

RECEIVED

SEP 02 1982

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set a 4 1/2" cement retainer at approximately 4900'. Squeeze cement perforations 5048' - 5536' with 150 cu. ft. Class B cement with 1/4# flocele and 2% CaCl₂. Leave 10 cu. ft. of cement on top of retainer. Spot a cement plug inside 4 1/2" csg. 2810' - 3075' with 25 cu. ft. Class B cement. Spot a cement plug inside 4 1/2" csg. 2020' - 2250' with 20 cu. ft. Class B cement. Spot a cement plug 0' - 285' with 25 cu. ft. Class B cement. Remove wellhead. Weld 3/4" plat over casing. Install 4" x 6' well marker.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *DeLasso Loos*
DeLasso Loos

TITLE District Manager

DATE September 1, 1982

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

NMOCC

APPROVED

SEP 3 1982

Forrest Keller
DISTRICT ENGINEER