

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
2. NAME OF OPERATOR
Blackwood & Nichols Co., Ltd.
3. ADDRESS OF OPERATOR
P. O. Box 1237, Durango, CO 81301
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' F/SL - 1080' F/WL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

NOV 16 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF 079042
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME NEBU Agreement
No. 1, Sec. 929
8. FARM OR LEASE NAME
Northeast Blanco Unit
9. WELL NO.
3X
10. FIELD OR WILDCAT NAME
Blanco Mesaverde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
L-5-30N-7W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
30-039-007910
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6233' KB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On November 12, 1982 pulled 2 3/8" tubing. Set a 4 1/2" cement retainer at 4910'. Squeeze cemented below retainer with 150 cu. ft. Class B cement with 1/4# flocele/cu. ft. and 2% CaCl₂. Pulled out of retainer. Spotted Class B cement 4810' - 4910'. Spotted cement plugs 2810' - 3075', 2020' - 2250' with Class B cement. Spotted a cement plug 0' - 290' with Class B cement. Removed wellhead. Welded 1" steel plate over casing. Installed 4" x 6' well marker.

RECEIVED

JUL 12 1984

OIL CON. DIV.
DIST. 3

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] District Manager DATE November 15, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC