

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-1115
Expires September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attn: John Hampton

3. Address and Telephone No

P.O. Box 800, Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

915' FSL and 1785' FEL SEC. 18, ~~E30N~~-R8W

5. Lease Designation and Serial No

SF 078596a

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Florance 102

9. API Well No.

30 045 12193

10. Field and Pool, or Exploratory Area

Blanco Pictured

11. County or Parish, State

Cliffs

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or
Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Amoco Production Company Plugged and Abandoned the above subject well.

1. Set cmt. retainer @ 1800'.
2. Sting into retainer x attempted to load annuuls, unable to do so. Pmp 92 sx class B cmt w 2% CACL2. Sting out of retainer.
3. Tag cmt. @ 1390' x pull up to 1375'.
4. Set pkr @ 576' x load annulus, psi to 500 for 20 min. Held.
5. Attempted to lead annulus @ 600 psi, unable to pres. up on tbq. tried to reset pkr. could not do so. Set cmt plug @ 790' x pmp 34 sx class B cmt w/ 2% CACL2.
6. Tag cmt @ 858'.
7. Pmp 50 BBLs FW down annuuls @ 2 BPM @ 150 psi. Slight blow @ Bradenhead 1 st 20 BBLs.
8. Pmp 150 sx class B cmt w/ 2% CACL2 @ 2 BPM. Displaced to 575'. Run temp survey.
9. Top cmt @ 390'.

CONTINUED ON FOLLOWING PAGE:

14. I hereby certify that the foregoing is true and correct

Signed

John Hampton

Title

Sr. Staff Admin. Supv.

Date

8-13-90

(This space for Federal or State office use)

Ken Townsend

Approved by

Conditions of approval, if any:

Title

NMOCD

Date

FLORANCE 102

CONTINUED:

10. Perf 4JSPF @ 270' and Break circulation thru bradenhead.
11. Tag hard cmt plug @ 510'.
12. Pmp 120 sx class G cmt. to surf.
14. Weld on cap x dry hole marker; reclaim location.

If you have any questions please contact Cindy Burton @ 830-5119.