

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole (Temporarily Abandoned)		5. LEASE DESIGNATION AND SERIAL NO. I-89-IND-58
2. NAME OF OPERATOR PAN AMERICAN PETROLEUM CORPORATION		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Tribal
3. ADDRESS OF OPERATOR 501 Airport Drive, Farmington, New Mexico 87401		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FSL and 1650' FKL		8. FARM OR LEASE NAME U.S.G. Section 19
14. PERMIT NO.		9. WELL NO. 24
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5114' GL, 5119' KB		10. FIELD AND POOL, OR WILDCAT Magbank Dakota
		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Section 19, T-29-N, R-16-W
		12. COUNTY OR PARISH San Juan
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Supplemental Well History

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well was spudded 9-23-67 and drilled to 57' where 7", 20 lb. casing was set and cemented with 35 sacks. Well was then drilled to 740' where logs were run. Well was then drilled to 755' where 4-1/2" casing was set and cemented with 125 sacks. Drilled into Dakota to 762' and allowed to flow for test. Well subsequently flowed 197 barrels of water with a trace of oil. Well was acidized 10-7-67 with 250 gallons 7-1/2% HCl. Subsequent testing recovered 236 barrels water with no oil. Well was temporarily abandoned 10-11-67 for possible future use as water disposal well.



RECEIVED

OCT 16 1967

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

L. A. Dwyer
L. A. Dwyer

TITLE

Petroleum Engineer (SG)

DATE

October 13, 1967

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229

997-851

