

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

RECEIVED
BLM

Sundry Notices and Reports on Wells

97 FEB 19 PM 3:09

1. Type of Well
GAS

RECEIVED
FEB 24 1997

070 FARMINGTON, NM

2. Name of Operator **OIL CON. DIV.**
BURLINGTON DIST. 3
RESOURCES
OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1750' FNL, 1610' FWL, Sec. 1, T-29-N, R-10-W, NMPM
F

5. Lease Number
NM-04241
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Sunray F #3
9. API Well No.
30-045-20361
10. Field and Pool
Basin Dakota
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
☐ Notice of Intent	☒ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☐ Other -
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

1-16-97 MIRU. SDON.
1-17-97 ND WH. NU BOP. PT BOP. TIH, tag CIBP @ 6680'. Load hole & circ clean w/63 bbl wtr. PT csg to 500 psi, failed. Plug #1: pump 13 sx Class "B" neat cmt @ 6503-6680'. WOC. TOOH w/199 jts 2 3/8" tbg. SD for weekend.
1-20-97 TIH w/4 1/2" gauge ring to 6000', perf 3 sqz holes @ 5921'. TOOH. TIH w/4 1/2" cmt retainer, set @ 5871'. TOOH. TIH, load hole w/2 bbl wtr. PT csg to 500 psi, failed. Establish injection. Plug #2: pump 43 sx Class "B" neat cmt outside csg below cmt retainer. Pump 8 sx Class "B" neat cmt inside csg @ 5764-5871'. TOOH to 4070'. Load hole w/4.5 bbl wtr. Plug #3: pump 20 sx Class "B" neat cmt @ 3800-4070'. TOOH to 2423'. Load hole w/4 bbl wtr. Plug #4: pump 104 sx Class "B" neat cmt in two stages @ 1036-2423'. TOOH. SDON.
1-21-97 TIH, tag TOC @ 2175'. Load hole w/7 bbl wtr. PT csg to 500 psi/5 min, OK. Plug #5: pump 85 sx Class "B" neat cmt inside csg @ 1026-2175'. TOOH. TIH, perf 3 sqz holes @ 274'. TOOH. Establish circ down csg & out bradenhead w/7 bbl wtr. Plug #6: pump 113 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Fill 4 1/2" csg & 9 5/8" annulus w/10 sx Class "B" neat cmt. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 1-21-97.

14. I hereby certify that the foregoing is true and correct.

Signed *Regulatory Administrator* Title Regulatory Administrator Date 2/17/97

(This space for Federal or State Office use)

APPROVED BY /s/ Duane W. Spencer

Title

Date FEB 21 1997

CONDITION OF APPROVAL, if any:

NMOC