

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078110

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal I

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

wildcat

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T29N, R14W

12. COUNTY OR PARISH
San Juan13. STATE
N. M.1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Dugan Production Corp.

3. ADDRESS OF OPERATOR

Box 234, Farmington, N. M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1100' fnl 1600' fw1

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5552' Gr.

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Completion

XX

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/24/69 PBD 1251' Perforated Pictured Cliffs from 1203' - 08' with Gowinder gun, 2/ft. S.W.F. with Dowell, 15,700 gal. water, 10,000# 20-40 sd., 2 1/2# J-166/1000 gal., I.F. 2400 psi., ave. 2050 psi, max. 2400 psi., min. 1900 psi. Ave. I.R. 19 B/M. Instant shut in 700 psi, 15 min. 300 psi, on vac in one hr. Perf. Fruitland formation 860' - 865' w/24 gram glass jets - 2/ft. Drop 15 rubber balls. Followed w/250 gal. 15% HCl. - frac pressure indicated balls hit and Fruitland broke down, frac Fruitland w/15,700 gal. water, 10,000# 10-20 sd. I.F. 2500 psi., ave. 1700 psi, min. 1500 psi., final 2500 psi. Instant shut in 800 psi, 15 min. 600 psi. Ave I.R. 19 B/M.



18. I hereby certify that the foregoing is true and correct

SIGNED

Certified by T. R. Dugan

TITLE

Engineer

DATE 3/12/69

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229

