Form 3160-5 (June 1930)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 5. Lease Designation and Serial No.

I-89-In-1-56

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I. Type of Well Oil Well 8. Well Name and No. Naves'o 77 10. Field and Pool, or Exploratory Area Rafflesas Ke - DK
11. County or Parish, State 1 920'FEL Sec 2. T29N, R 18W San Jusa, Nom CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Well was premoisly PTA 3-1- ...

though oil & Gas intermittently. See attacked

procedumento re-play the well.

DECEIVED

No. 37 Well was premoisly PTA 5-15-72. Well presently

14. I hereby certify that the foregoing is true and correct Signed	Title Engineer	Date 5- 7.7-94
(This space for Pederal or State office use) Approved by Conditions of approval, if any:	Title	ARFROVED
	NMOCD	MAY 8 7 1904
Fitle 18 U.S.C. Section 1001, makes it a crime for any person knowing	ngly and willfully to make to any department or agency	of the United State of Wilder

or representations as to any matter within its jurisdiction

Navajo #47 (Dk) NE, Sec. 2, T29N, R19W San Juan County, New Mexico

Wireline Work (5-18-94)

Ran 1"/16" sinker bar from surface to 625' (627' KB). POH with no problems.

PLUG AND ABANDONMENT PROCEDURE:

(Cement volume unknown, will mix and pump until good cement returns at surface)

- 1. Prepare blow pit. Comply to all BLM, and Harken safety rules and regulations.
- 2. Build wooden platform over top of wellbore hole using timbers and plywood.
- 3. RIH with one joint 1" steel tubing (with perfs) and approximately 630' of Quail PE 3408 High Density Polyethylene 1-1/4" pipe (continuous, 630# burst) to as deep as possible (627' KB).
- 4. Load well with water and establish circulation to surface.
- 5. Plug #1 (Dakota to surface): Mix and pump cement from 627' (+/-) until good cement circulates to surface. (Estimated cement volume 300 to 600 sxs).
- 6. Release polypipe and WOC.
- 7. Fill wellbore at surface as necessary with cement.
- 8. Install P&A marker with cement.
- 9. Reclaim location.

EXISTING WELL

HARKEN SOUTHWEST 19 MAY 94 **NAVAJO #47 (Dk)** NE, Sec. 2, 29N, 19W San Juan County, NM

SURFACE CRATER 10' DIAMETER

AT APPROXIMATELY 20' THE WELLBORE IS 2' DIAMETER

Greenhorn @ 628'

Dakota A @ 713'

TD 744"

Wireline TD @ 627'

Reported Cement Plug

16 sxs - 744' - 644'

6-1/4" HOLE

19 MAY 94

EXISTING WELL

HARKEN SOUTHWEST NAVAJO #47 (Dk) NE, Sec. 2, 29N, 19W San Juan County, NM

SURFACE CRATER 10' DIAMETER

AT APPROXIMATELY 20'
THE WELLBORE IS 2' DIAMETER

Greenhorn @ 628'

Dakota A @ 713'

TD 744"

6-1/4" HOLE

Wireline TD @ 627'

Reported Cement Plug

16 sxs - 744' - 644'

Pertinent Data Sheet

19 May 94 Page 1 of 2

Wellname: Navajo #47

Field:

Rattlesnake

Well Type: Dakota

Elevation:

5293' GR

Location:

1650' FNL & 990' FEL

San Juan Co., New Mexico

Ownership:

N/A·

Drilling:

Spud Date: 7-5-69

Total Depth:

744'

Casing and Tubing:

Hole Size Size, Wt, & Grade

Depth

Cement

8 3/4"

7", 24#

16'

5 sxs

Surf.

Note:

Well records do not report production casing being set in this well.

Formation Tops:

Greenhorn 628'

Dakota A

713'

Well History:

6-17-69

APD by Eastern Petroleum

12-18-69

Sundry Notice by Eastern Petroleum Company

* 7" surface casing set at 16' with 5 sxs cement

* Dakota ss top at 713'

* TD - 744'

* Dakota formations tight and dry

* Propose to P&A

- 100' plug 744-644 with 16 sxs cement

- 10' surface plug with 3 sxs cement

1-23-70

Well Completion Report filed by Eastern Petroleum Company

5-15-72

Sundry Notice by Eastern Petroleum Company

* "Set plugs as per Sundry Notice dated 12-18-69. Erected a

4 ft marker."

6-91

Well venting gas and unloading fluids occasionally at base of

dry hole marker.

5-94

Well venting gas and occasionally unloads fluids; this unloading has developed a large crater, approximately 10' diameter, which

has caused the 7" surface casing and dry hole marker to fall to

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT FARMINGTON DISTRICT OFFICE 1235 La Plata Highway Farmington, New Mexico 87401

Attachment to Notice of

Re: Permanent Abandonment

Intention to Abandon

Well: 47 Navajo

CONDITIONS OF APPROVAL

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Leases."
- 2. Mike Flaniken with the Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907.
- 3. The following modifications to your plugging program are to be made (when applicable):

Office Hours: 7:45 a.m. to 4:30 p.m.