Budget Bureau No. 1004-0135 UNITED STATES

SUBMIT IN TRIPLICATE*

(Other instructions on reverse side) Ferm 3160-5 Expires August 31, 1985 (November 1983) 5. LEASE DESIGNATION AND SERIAL NO (Formerly 9-331) #14-20-603-1049 BUREAU OF LAND MANAGEMENT IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) Navajo 7. UNIT AGREEMENT NAME Depleted Reference 14-20-603-1049 (WC) WELL WELL X 3162.3-4 (016) S FARM OR LEASE NAME NAME OF OPERATOR Texas Eastern Developments. Inc. S WELL NO. P. O. Box 2521 Houston, IX 77252-2521

Location of Well (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

APR 1 0 1 85 Navajo 17H 10. FIELD AND POOL, OR WILDCAT APR 1 n 1987 Shiprock-Gallup
11. Sec., T., R., M., OR BLE. AND
SURVEY OR AREA 1309 ' FE L RUREAU OF LAND MANAGEMENT 1989 ' FN L & **FARMINGTON RESOURCE AREA** Sec. 17, T29N, R18W 15 ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO 5195.30 GR. NM San Juan Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data SIRSEOURNT REPORT OF : NOTICE OF INTENTION TO: REPAIRING WELL WATER SHUT-OFF PULL OR ALTER CASING TEST WATER SHUT-OFF ALTERING CASING FRACTUBE TREATMENT MULTIPLE COMPLETE FRACTI RE TREAT SHOOTING OR ACIDIZING ABANDON MENT® ABANDON* SHOOT OR ACIDIZE CHANGE PLANS REPAIR WELL (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETE: OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) * (Other) Well Data Spud /1/16/69 TD /08 Hole Size 612 Casing 41/2 @ /03 ' cmt'd w/ — Amount Casing Recovered: Size 94'-98' Producing interval: Method of Plugging: Halliburton Pump Type Cement: Portland w/8% Bentonite, slurry wt. 13.3 ppg, slurry vol. 1.82 cu ft/sx. Remove rods, pump and tubing. cu ft. 6.5 cu ft, set plug 1st stage cement: Squeeze Top cement at OGR. culift cement. _' to surface w/ 2nd stage cement: set plug -Dates Notice of intent to plug approved: JAN. 30, 1987 Approved so to plugging of the soul Colum Liability under band is retained until Well plugged: MARCH 13,1987 surface restoration is completed. Land Restored: MARCH 19, 1987 Marker set: MARCIS 26,1987 Land seeded: 18. I hereby certify that the foregoing is true and correct SIGNED H. TITLE Drilling Superintendent M. N. Hinds (This space for Federal or State office use) TITLE APPROVED BY CONDITIONS OF APPROVAL, IF ANY: ELAPSEA MANAGER FARMINGTON SESSUINCE ANTA