

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821 SEP 30 1999

Location of Well (Footage, Sec., T., R., M., or Survey Description)

1700 FNL & 1800 FEL (SW/4 NE/4)
Unit G, Sec. 31, T29N, R13W, NMPM

5. Lease Designation and Serial No.

SF 078931-B

6. If Indian, Allotted or Tribe Name

7. If Unit or CA, Agreement Designation

Central Cha Cha Unit

8. Well Name and No.

Central Cha Cha Unit #7

9. API Well No.

30 045 20787

10. Field and Pool, or Exploratory Area

Cha Cha Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plan to plug well as follows:

1. Set cast iron bridge plug 50' below Gallup top (5188') at 5240'.
2. Spot 100' Class "B" cement plug on top of bridge plug.
3. Spot 100' Class "B" cement plug inside casing across Mesaverde top (2423')
4. Spot Class "B" cement plug across Pictured Cliffs top (1505') and Fruitland top (1207') inside casing.
5. Spot Class "B" cement plug 50' below surface casing (217') from 267' to surface.
6. Attempt to pump down surface casing annulus. If pump rate established, pump cement down surface casing/production casing annulus to cover from 50' below surface casing to surface.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander
John Alexander

Title

Vice-president

Date

8/31/99

(This space for Federal or State office use)

Approved by

A. T. L.
A. T. L.

Title

Date

9-28-99

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

WMOG