

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1040' FSL 1780' FEL, Sec. 11, T-29-N, R-10-W, NMPM

5. Lease Number  
SF-077092

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

Well Name & Number

Lackey A #5

API Well No.

30-045-20790

10. Field and Pool

Aztec Pictured Cliffs

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other - tubing repair

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to repair the tubing on the subject well according to the attached procedure.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] (KLM5) Title Regulatory Administrator Date 9/15/98

TLW

(This space for Federal or State Office use)

APPROVED BY [Signature] Title Spencer

Date JAN - 7 1999

CONDITION OF APPROVAL, if any

HMOC

**Lackey A #5**  
**Pictured Cliffs**  
**1040' FSL & 1780' FEL**  
**Unit O, Section 11, T29N, R10W**  
**Latitude / Longitude: 36° 44.1467' / 107° 51.0526'**  
**DPNO: 52410A**  
**Tubing Repair Procedure**

**Project Summary:** The Lackey A #5 was drilled in 1971. The tubing has not been pulled since originally installed. Gas production cannot flow up the tubing. We propose to pull the tubing, check for fill, and replace any worn or scaled tubing.

1. Hold safety meeting. Comply with all NMOCD, BLM and Burlington safety and environmental regulations. Test rig anchors and build blow pit prior to moving in rig. **Notify BROG Regulatory (Peggy Bradfield 326-9727) and the appropriate Regulatory Agency prior to pumping any cement job. If an unplanned cement job is required, approval is required before the job can be pumped. If verbal approval is obtained, document approval in DIMS/WIMS.** Allow as much time as possible prior to pump time in case the Agency decides to witness the cement job.
2. MOL and RU workover rig. Obtain and record all wellhead pressures. NU relief line. Blow well down and kill with 2% KCL water if necessary. NU BOP with stripping head. Test and record operation of BOP rams. Have wellhead and valves serviced as necessary. Test secondary seal and replace/install as necessary.
3. The Pictured Cliffs tubing is 1-1/4", 2.4#, J-55 with 3' perforation joint and bull plug on bottom set at 2293'. Release donut, pick up additional joints of tubing and tag bottom (record depth.) PBTD should be at +/- 2336'. TOO H with tubing. Visually inspect tubing for corrosion and replace any bad joints. Check tubing for scale build up and notify Operations Engineer.
4. If fill covers any perforations then TIH with open ended 1-1/4" tubing and notched collar cleaning out with air/mist. PU above the perforations and flow the well naturally, making short trips for clean up when necessary. TOO H with tubing. **NOTE: When using air/mist, minimum mist rate is 12 bph.**
5. TIH with one joint of 1-1/4" tubing with an expendable check on bottom and a seating nipple one joint off bottom. Run a broach on sandline to insure that the tubing is clear. Land tubing at approximately 2250'. ND BOP and NU WH. Pump off expendable check. Connect to casing and circulate air to assure that expendable check has pumped off. If well will not flow on it's own, make swab run to SN. RD and MOL. Return well to production.

Recommended: Kevin Midkiff 9/11/98 Operations Engineer Approved: Bruce D. Brey 9.14.98 Drilling Superintendent

Kevin Midkiff  
Office - 599-9807  
Pager - 564-1653