Form: \$1,60-5' UNITED ST/	ATES SUBMIT IN TRIPLICATE	Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985
November 1983) Formerly 9-331) DEPARTMENT OF THE INTERIOR (Other Instructions on re-		5. LEASE DESIGNATION AND SERIAL NO. NOG-8202-1116
SUNDRY NOTICES AND (Do not use this form for proposals to drill or to Use "APPLICATION FOR PERM	REPORTS ONEWELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME NAVAJO
OIL X GAS	89 FEB -2 AMII: 11	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR CHUSKA ENERGY COMPANY	FARMINGTON RESOURCE AREA FARMINGTON, NEW MEXICO	8. PARM OR LEASE NAME RATTLESNAKE -3-2-29N19W
3. ADDRESS OF OPERATOR 315 N. BEHREND, FARMINGTON, N.M 87401		9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		10. FIELD AND POOL, OR WILDCAT RATTLESNAKE DAKOTA
500° FEL & 2100° FSL		11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA 2-T. 29N-R. 19W
14. PERMIT NO. 15. SIZVATIONS (Show whether DF, ST, GR, etc.)		12. COURTY OR PARISH 18. STATE
		SAN JUAN N.M
16. Check Appropriate Box	To Indicate Nature of Notice, Report, or	Other Data
TEST WATER SHUT-OFF PRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other) 17. PESCEIBE PROPOSED OR COMPLETED OPERATIONS (Clearly proposed work. If well is directionally drilled. given nent to this work.)* This well was originally knownent to this work.) The well will be re-entered steel test tank. Depending on results of test through with a liner and cement perforated and stimulated. Ex A general operational porced.	state all pertinent details, and give pertinent date subsurface locations and measured and true vertoes to flow test Dakota sand to pen hole section and the Dakota formation and procedure will depend and true vertoes to flow the section and the section and the pen hole section and the procedure will depend and true vertoes to flow the section and the section and the section and the procedure will depend and true vertoes the section and the se	erated by Eastern by swabbing into a n 835-845 may be cased n can then be
18. I hereby certify that the foregoing is true and correct	ct	MAR 0 2 1989 OIL CON. DIV. DIST. 3
81GNED SIGNED COLOR OF SIGNED	TITLE Production Mgr.	DATE 2-1-25
(This space for Federal or State office use)		APPROVED
APPROVED BY	TITLE	
•	See Instructions on Reverse Side	Jan

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



OIL CON. DIV

Workover and Testing Prognosis Rattlesnake Dakota Field San Juan Co., New Mexico

Nine (9) wells in the Rattlesnake Dakota Field are to be reentered and tested by Chuska Energy Company. These wells are all at least 26 years old and a lot of the well information is either incomplete or missing. We have inspected the area and found at least six (6) of the wells are capable of flowing oil at this time. Because of the nature of the wells and the lack of information we propose to submit a general re-entry procedure and AFE. Specific procedures will be impossible to write until we determine exact well bore configurations and producing capabilities. Following is an outline of the re-entry procedure:

- 1. Conduct archaeological clearance of well sites and access roads of those wells slated for re-entry.
- 2. Clear land damages to obtain access to wells.
- 3. Submit sundry notices and obtain water permits.
- 4. Move in test tanks and test each of the following wells that have been determined to be capable of flowing:

Rattlesnake 3-1-29N19W No. 1 (Old Well No. Unknown)	1765' FSL & 307' FWL 1- Twn.29N-Rng. 19W
Rattlesnake 3-2-29N19W No. 1 (Old Well No. Unknown)	2309' FNL & 2192' FWL 2- Twn.29N-Rng. 19W
Rattlesnake 3-2-29N19W No. 3 (Old Well No. 207)	2450' FSL & 725' FEL 2- Twn.29N-Rng. 19W
Rattlesnake 3-2-29N19W No. 4 (Old Well No. 205)	2450' FSL & 330' FEL 2- Twn.29N-Rng.19W
Rattlesnake 3-12-29N19W No. 2 (Old Well No. 148)	940' FSL & 1653' FWL 12- Twn.29N-Rng.19W
Rattlesnake 3-12-29N19W No. 5 (Old Well No. 149)	2008' FSL & 2348' FEL 12- Twn.29N-19W

Each well will be flowed at a low rate to prevent water from coning. A separate test tank will be used at each site to obtain accurate test data. Further work procedures on these wells will depend on test results.

5. The remaining three wells have fluid at or near the surface, but will not flow. The general procedure for these wells will be to run a slick line survey to determine well depth. A casing scraper and bit will be run to bottom to clean up the

LAMUS 1889 JIL COM. DIV. DIST. 3

casing and clear any formation debris in the hole. If the well contains 5 1/2" or grater casing, consideration will be given to running a GST (Carbon-Oxygen) log to determine the oil-water contact and passed up oil zones. Based on the log results, the well may be swabbed to test production. If it is determined that an oil-water contact exists in such manner that may cause water to be produced, a liner may be cemented in the hole. The liner would consist of either 2 3/8" or 2 7/8" tubing (depending on casing size). The Dakota would then be perforated in the oil zone and cleaned up with acid. A production test would then follow. The wells that will be tested in the above manner follow:

Rattlesnake 3-12-29N19W No.1 (Old Well No. 154)	900' FNL & 1650' FWL 12- Twn.29N-Rng.19W	
Rattlesnake 3-2-29N19W No. 2 (Old Well No. 210)	2100' FSL & 500' FEL 2- Twn.29N-19W.	
Rattlesnake 3-12-29N19W No.4 (Old Well No. 152)	2275' FNL & 2440' FWL 12- Twn.29N-Rng.19W	
6. If the wells that are to be tesponded procedure similar to that in step to	ted by flowing cease to flow, a 5 may be initiated in them.	
APPROV	AL	
Recommended:	2	
Production Manager July Alexand Date: 1		
sheraror upbrovar:	_	
J.P. Production M.C. MAR	Date: 1/18/89	
President	Date:	
Chairman of Board	Date:	
Non-Operator Approval:		
Name:	Date:	
`aaaanya		