| Form | 3160-5 |
|-------|--------|
| (June | 1990\ |

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

| PORM APPROYED |
|----------------------------|
| Budget Bureau No. 1004-013 |
| Expires: March 31, 1993 |
| 1 2 1 1 1 1 1 1 No |

| | | 14- | 20-0 6 | οU | 3-1 | OOO | 9 |
|----|---|---------|-------------------|----|-------|------|---|
| 6. | Ħ | ladies, | Allottee | or | Tribe | Name | |

| | SUNDRY NOTICES AND REPORTS ON WELLS | um 1 : |
|-----------------|---|--------------|
| Do not use this | form for proposals to drill or to deepen or reentry to a different Use "APPLICATION FOR PERMIT—" for such proposals | t reservoir. |
| | | |
| | | |

| SUBMIT IN TRIPLICATE | 070 F. Marian Marian, 104 | 7. If Unit or CA, Agroement Designation |
|--|---------------------------|---|
| 1. Type of Well Other P&A P&A | · I | 8. Well Name and No. |
| 2. Name of Operator | | North Hogback 7#3 |
| Raymond T. Duncan | | 9. API Well No. |
| 3. Address and Telephone No. | | |
| P. O. Box 420, Farmington, NM 87499 (505 |) 325–1821 | 10. Field and Pool, or Exploratory Area |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) | | Slickrock Dakota |
| 1810' FNL - 330' FWL | | 11. County or Parish, State |
| Sec. 7, T29N, R16W, NMPM | | San Juan, NM |


| TYPE OF SUBMISSION | TYPE OF ACTION | | |
|--------------------------|-------------------------------|---|--|
| Notice of Intent | Abandonment | Change of Plans | |
| Subsequent Report | Recompletion Plugging Back | New Construction Non-Routine Fracturing | |
| Final Abandonment Notice | Casing Repair Altering Casing | Water Shut-Off Conversion to Injection | |

be Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estin give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug well as follows:

Fill 4½" casing 0-725'. Pump 11 bbls water. Break down @ 1500 psi. Cement with 65 cu. ft. class "B" neat. 2 BPM @ 400 psi. Break down @ 1500 Tag cement top @ 100'. Fill with 19 cu. ft. class "B" cement. Job complete 10-15-93.

> Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.



| | | 1000 8 |
|---|-----------|---------------|
| 4. I hereby certify that the foregoing is true and correct Signed | TideAgent | Date 10/28/93 |
| This space John Alexander | | |
| Approved by | Title | APPROVED |
| | | |

or representations as to any matter within its jurisdiction. *See Instruction on Reverse Side

Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States and